

B.E.G.**LUXOMAT®**

PD4-M-TRIO-DIM-FC

92735 EAN: 4007529927357

- Voltage: 110 – 240 V AC 50 / 60 Hz
- Dimensions: FC= Ø 117 x 100 mm
- Power consumption: approx. 0.6 W

Areas of application

- open-plan offices
- conference rooms
- classrooms/seminar rooms

Order data

Designation	Colour	Art.No
PD4-M-TRIO-DIM-FC	white	92735

Accessories

Designation	Colour	Art.No
BLE-IR-Adapter	black	93067
IR-PD4-TRIO	-	92097
Wire basket BSK (Ø 200 x 90 mm)	white	92199
Wire basket BSK (Ø 164 x 143 mm)	white	92467
RC-Arc extinction kit	white	10880
Mini-RC-Arc extinction kit		10882
Socket IP54 PD4-TRIO-SM	white	92386

Technical data

Voltage:	110 – 240 V AC 50 / 60 Hz
Dimensions:	FC= Ø 117 x 100 mm
Power consumption:	approx. 0.6 W
Detection area:	horizontal 360° (Ceiling mounting) max. Ø 24 m across max. Ø 8 m towards max. Ø 6.4 m seated
Range:	
Monitored area (tangential movement):	450 m² / 2.5 m mounting height
Mounting height min./max./recommended:	2 m / 10 m / 2.5 m
Degree / class of protection:	FC= IP20 / Class II
Impact strength:	IK04
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant
Material color:	white mat, similar to RAL9010
Channel 1 and Channel 2 (lighting control)	
Switching power:	3000 W, $\cos \varphi = 1$ 1500 VA, $\cos \varphi = 0.5$ 300 W LED max. inrush current I_p (20 ms) = 165 A max. inrush current I_p (200 µs) = 800 A
Type of contact (k):	1x µ-contact, NO contact with tungsten pre-make contact
DIM output:	2 dim outputs 1-10 V DC, up to 25 ballasts per channel
Orientation light:	20 % / OFF / ∞
Channel 3 (HVAC control or lighting control, potential-free (dry))	
Switching power:	3000 W, $\cos \varphi = 1$ 1500 VA, $\cos \varphi = 0.5$ 300 W LED max. inrush current I_p (20ms) = 165 A, (200 µs) = 800 A

Product information

Occupancy detector for two separate lighting groups, for daylight-dependent lighting control

One potential-free switching channel for control of equipment (HVAC) or lighting

One common detection area

Two independent, movable light sensors

Manual switching and dimming via push button possible

Orientation light function

Relay with tungsten pre-make contact, optimised for LED loads

Version as master device

Detection area can be extended by using slave devices

Two 1-10 V interfaces for control of dimmable electronic ballasts

Additional functions can be set up using the optional remote control.

Avoidance of standby losses of the lighting system in accordance with EnEV DIN V 18599-4

Application examples:

open-plan offices, conference rooms, classrooms/seminar rooms

Type of contact:

1x μ -contact, dry
NO contact with
tungsten pre-
make contact

Channel 1 to channel 3

Follow-up time:




1 min – 60 min

Brightness set value:

10 – 2000 Lux

Light measuring:

Mixed light
measuring



Order data


Designation	Colour	Art.No	EAN
PD4-M-3C-TRIO-FC-92745	white	92745	4007529927456
PD4-M-2C-DUO-FC-92251	white	92251	4007529922512
PD4-M-3C-TRIO-SM-92740	white	92740	4007529927401

Accessories




BLE-IR-Adapter
Art.No: 93067

Dimensions: 40 x 55 x 103 mm
Material color: black
Frequency: 2.4 GHz ISM band, GFSK 0.2 dBm + 5.3 dBi = 5.5 dBm



IR-PD4-TRIO
Art.No: 92097

Battery: 3.0 V Lithium CR2032 (inclusive)
Dimensions: 80 x 60 x 8 mm
Material color: -



Wire basket BSK (Ø 200 x 90 mm)
Art.No: 92199

Dimensions: Ø 200 x 90 mm
Impact strength: IK09
Housing: coated steel basket



Wire basket BSK (Ø 164 x 143 mm)
Art.No: 92467

Dimensions: Ø 164 x 143 mm
Impact strength: IK09
Housing: coated steel basket



RC-Arc extinction kit
Art.No: 10880

Voltage: 230 V AC ±10%
Dimensions: 38 x 12 x 26 mm
Degree / class of protection: IP20 / Class II



Mini-RC-Arc extinction kit
Art.No: 10882

Voltage: 230 V AC ±10%
Dimensions: 50 x 23 x 8 mm
Degree / class of protection: IP20 / Class II



Socket IP54 PD4-TRIO-SM

Art.No: 92386

Degree / class of protection: IP54

Housing: polycarbonate, UV-resistant

Material color: white