

**B.E.G.****LUXOMAT<sup>®</sup> net**

## BIA-4-KNX REG

Prod.No. 90405 EAN: 4007529904051

Compact binary input with 4 channels for controlling luminaires, blinds, etc

The inputs can be controlled via conventional switches with an external voltage of 12 to 230 V

Use as a pulse counter is possible

### Order data

Designation	Colour	Art.No
BIA-4-KNX REG	-	90405

## Technical data

Voltage:	via KNX BUS
Dimensions:	60 x 18 x 90 mm (1 TE)
Typ. power input:	5 mA
Degree / class of protection:	IP20 / Class II
Ambient temperature:	-5 °C to +45 °C
Housing:	polycarbonate, UV-resistant
Material color:	-
KNX TP 256:	Yes
	1 x Bus line: EIB/KNX bus terminal (black/red)
Connections and wires:	6 x Screw terminals 0.34 ... 2.5 mm <sup>2</sup> rigid 0.34 ... 2.5 mm <sup>2</sup> fine-wired

## Product information

Compact binary input with 4 channels for controlling luminaires, blinds, etc

The inputs can be controlled via conventional switches with an external voltage of 12 to 230 V

Use as a pulse counter is possible

Two push-buttons and three LEDs enable local operation and visualisation of the unit's status

In addition to the input channels, the unit contains 16 independent logic or time functions



