

**B.E.G.**

**LUXOMAT® net**



## BIA4-KNXs REG

Prod.No. 90411 EAN: 4007529904112

Compact binary input with 4 channels for controlling luminaires, blinds, etc

KNX Secure ready

Galvanically isolated inputs for external voltage from 12 to 230 V

### Order data

Designation	Colour	Art.No
BIA4-KNXs REG	-	90411

## Technical data

Voltage:	via KNX BUS
Dimensions:	55 x 18 x 90 mm (1 TE)
Typ. power input:	3 mA
Degree / class of protection:	IP20 / Class II
Ambient temperature:	-5 °C to +45 °C
Housing:	polycarbonate, UV-resistant
Material color:	-
KNX TP 256:	Yes
KNX Secure:	Yes
Connections and wires:	1 x KNX bus terminal black/red 6 x Screw terminals 0.34 ... 2.5 mm <sup>2</sup> rigid 0.34 ... 2.5 mm <sup>2</sup> fine-wired

## Product information

Compact binary input with 4 channels for controlling luminaires, blinds, etc

KNX Secure ready

Galvanically isolated inputs for external voltage from 12 to 230 V

Use as a pulse counter is possible

Two push-buttons and three LEDs enable local operation and visualisation of the unit's status

In addition to the input channels, the unit contains 16 independent logic or time functions



