

**B.E.G.****LUXOMAT<sup>®</sup> net**

## BIP-4-KNX REG

Prod.No. 90406 EAN: 4007529904068

Compact binary input with 4 channels for controlling luminaires, blinds, etc

Inputs are designed for dry contacts

Use as a pulse counter is possible

### Order data

Designation	Colour	Art.No
BIP-4-KNX REG	white	90406

## Technical data

Voltage:	via KNX BUS
Dimensions:	60 x 18 x 90 mm (1 TE)
Typ. power input:	5 mA
Degree / class of protection:	IP20 / Class III
Ambient temperature:	-5 °C to +45 °C
Housing:	polycarbonate, UV-resistant
Material color:	white
KNX TP 256:	Yes
Connections and wires:	1 x Bus line: EIB/KNX bus terminal (black/red)
	6 x Screw terminals
	0.34 ... 2.5 mm <sup>2</sup> rigid
	0.34 ... 2.5 mm <sup>2</sup> fine-wired

## Product information

Compact binary input with 4 channels for controlling luminaires, blinds, etc

Inputs are designed for dry contacts

Use as a pulse counter is possible

Two push-buttons and three LEDs enable local operation and visualisation of the unit's status

In addition to the input channels, the unit contains 16 independent logic or time functions



