

B.E.G.

LUXOMAT[®] net



BIP4-KNXs REG

Prod.No. 90412 EAN: 4007529904129

Compact binary input with 4 channels for controlling luminaires, blinds, etc

KNX Secure ready

Galvanically isolated inputs for potential-free contacts

Order data

| Designation | Colour | Art.No |
|---------------|--------|--------|
| BIP4-KNXs REG | - | 90412 |

Technical data

| | |
|-------------------------------|--|
| Voltage: | via KNX BUS |
| Dimensions: | 55 x 18 x 90 mm (1 TE) |
| Typ. power input: | 5 mA |
| Degree / class of protection: | IP20 / Class III |
| Ambient temperature: | -5 °C to +45 °C |
| Housing: | polycarbonate, UV-resistant |
| Material color: | - |
| KNX TP 256: | Yes |
| KNX Secure: | Yes |
| Connections and wires: | 1 x KNX bus terminal black/red 6 x Screw terminals (binary input, max. 30m cable length) 0.34 ... 2.5 mm ² rigid 0.34 ... 2.5 mm ² fine-wired |

Product information

Compact binary input with 4 channels for controlling luminaires, blinds, etc

KNX Secure ready

Galvanically isolated inputs for potential-free contacts

Use as a pulse counter is possible

Two push-buttons and three LEDs enable local operation and visualisation of the unit's status

In addition to the input channels, the unit contains 16 independent logic or time functions



