

**B.E.G.**

**LUXOMAT®**



## BL4-C-FC Set 93284-93194

- Voltage: 110 - 240 V AC 50 / 60 Hz
- Dimensions: **Ø 104.5 x 84 mm + Ø 77 x 4.2 mm (93194)**
- Power consumption: approx. 0.3 W

### Areas of application

- corridors/hallways

### Order data

Designation	Colour	Art.No
BL4-C-FC	white	93284
Mounting set BL4-FM	white	93194

## Technical data

Voltage:	110 - 240 V AC 50 / 60 Hz
Dimensions:	<b>Ø 104.5 x 84 mm + Ø 77 x 4.2 mm (93194)</b>
Power consumption:	approx. 0.3 W horizontal 360°
Detection area:	(Ceiling mounting) max. Ø 32 m across max. Ø 16 m towards
Range:	
Monitored area (tangential movement):	200 m <sup>2</sup> / 2.5 m mounting height
Mounting height min./max./recommended:	2.4 m / 2.6 m / 2.5 m
Degree / class of protection:	IP20 / Class II
Impact strength:	IK04
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant white mat, similar to RAL9010
Material color:	
Connections and wires:	0.5 - 2.5 mm <sup>2</sup> for solid conductors

### Channel 1 (lighting control)

Switching power:	1000 W, $\cos \varphi$ = 1 500 VA, $\cos \varphi =$ 0.5 400 W LED
Type of contact (k):	1x $\mu$ -contact, NO contact
Follow-up time:	15 sec - 60 min
Switch-on threshold:	10 - 2000 Lux

## Product information

Set : BL4-C-FC + Mounting set BL4-FM white

Remote control-capable ceiling motion detector designed for corridors

For mounting in suspended ceilings

One channel for light switching

Zero crossing switching

Manual switching via push-button possible

### Easy operation with remote control (required)

Basic functions for cost-effective applications

Ready-to-operate thanks to factory settings

Accessory for surface mounting and flush mounting available

There are markings to ensure correct alignment during installation

Factory setting: High detection sensitivity, follow-up time 10 min, switch-on threshold 500 lux

High-performance relay designed for 100,000 switching cycles under high load, several million switching cycles possible under low load



## Set items

To receive the bundle according to the technical specification, please order the items listed.



### **BL4-C-FC**

Art.No: 93284

Voltage: 110 – 240 V AC 50 / 60 Hz

Dimensions: Ø 104.5 x 84 mm

Power consumption: approx. 0.3 W



### **Mounting set BL4-FM**

Art.No: 93194

Dimensions: Ø 77 x 4.2 mm

Material color: white