

**B.E.G.**

**LUXOMAT®**



## Indoor 180-S covering included Set 92135-92139

- Voltage: 110 - 240 V AC 50 / 60 Hz
- Dimensions: **covering included 87 x 87 x 61 mm + 87 x 87 mm (92139)**
- Power consumption: approx. 0.2 W

### Order data

Designation	Colour	Art.No
Indoor 180-S covering included	pure white	92135
Frame IP54 Indoor 180	pure white	92139

## Technical data

Voltage:	110 - 240 V AC 50 / 60 Hz
Dimensions:	<b>covering included 87 x 87 x 61 mm + 87 x 87 mm (92139)</b>
Power consumption:	approx. 0.2 W
Detection area:	horizontal 180° (Wall mounting) max. 10 m across max. 3 m towards
Range:	150 m <sup>2</sup> / 1.1 m mounting height
Monitored area (tangential movement):	1 m / 2.2 m / 1.1 m
Mounting height min./max./recommended:	<b>IP20 / Class II + IP54 (92139)</b>
Degree / class of protection:	IK05
Impact strength:	-25 °C to +50 °C
Ambient temperature:	polycarbonate, UV-resistant
Housing:	<b>pure white mat, similar to RAL9010 (92139)</b>
Material color:	2 or 9 sec
Pulse interval:	

## Product information

Set : Indoor 180-S covering included + Frame IP54  
Indoor 180 pure white mat, similar to RAL9010

Slave device

For extending the detection area of a Master device

Compatible with 230 V devices. Concerning exceptions please see the respective master device.

Available with covering (centre plate dimensions 60 x 60 mm) or without covering for use with covering (centre plate dimensions 50 x 50 mm) in 5 different colours

In combination with centre plates usable with current frame systems of various manufacturers

B.E.G. frames and centre plates for combination with other frame systems available



## Set items

To receive the bundle according to the technical specification, please order the items listed.



### **Indoor 180-S covering included**

Art.No: 92135

Voltage: 110 – 240 V AC 50 / 60 Hz

Dimensions: covering included 87 x 87 x 61 mm

Power consumption: approx. 0.2 W



### **Frame IP54 Indoor 180**

Art.No: 92139

Dimensions: 87 x 87 mm

Degree / class of protection: IP54

Housing: polycarbonate, UV-resistant