

B.E.G.

LUXOMAT®



Indoor 180-S covering included Set 92135-92631

- Voltage: 110 - 240 V AC 50 / 60 Hz
- Dimensions: covering included 87 x 87 x 61 mm
- Power consumption: approx. 0.2 W

Order data

Designation	Colour	Art.No
Indoor 180-S covering included	pure white	92135
Frame IP20 Indoor 180	traffic white	92631

Technical data

Voltage:	110 - 240 V AC 50 / 60 Hz
Dimensions:	covering included 87 x 87 x 61 mm
Power consumption:	approx. 0.2 W
Detection area:	horizontal 180° (Wall mounting) max. 10 m
Range:	across max. 3 m towards
Monitored area (tangential movement):	150 m ² / 1.1 m mounting height
Mounting height min./max./recommended:	1 m / 2.2 m / 1.1 m
Degree / class of protection:	IP20 / Class II
Impact strength:	IK05
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant
Material color:	traffic white mat, similar to RAL9016 (92631)
Pulse interval:	2 or 9 sec

Product information

Set : Indoor 180-S covering included + Frame IP20
Indoor 180 traffic white mat, similar to RAL9016

Slave device

For extending the detection area of a Master device

Compatible with 230 V devices. Concerning exceptions please see the respective master device.

Available with covering (centre plate dimensions 60 x 60 mm) or without covering for use with covering (centre plate dimensions 50 x 50 mm) in 5 different colours

In combination with centre plates usable with current frame systems of various manufacturers

B.E.G. frames and centre plates for combination with other frame systems available



Set items

To receive the bundle according to the technical specification, please order the items listed.




Indoor 180-S covering included

Art.No: 92135

Voltage: 110 – 240 V AC 50 / 60 Hz

Dimensions: covering included 87 x 87 x 61 mm

Power consumption: approx. 0.2 W



Frame IP20 Indoor 180

Art.No: 92631

Dimensions: 86 x 86 mm

Degree / class of protection: IP20

Housing: polycarbonate, UV-resistant