

B.E.G.**LUXOMAT®**

Indoor 180-S covering not included Set 92660-92139-92141

- Voltage: 110 - 240 V AC 50 / 60 Hz
- Dimensions: **88 x 88 x 42 mm (92141)**
- Power consumption: approx. 0.2 W

Order data

| Designation | Colour | Art.No |
|------------------------------------|------------|--------|
| Indoor 180-S covering not included | - | 92660 |
| Frame IP54 Indoor 180 | pure white | 92139 |
| Surface mounting socket Indoor 180 | pure white | 92141 |

Technical data

| | |
|-------------------------------------------|---------------------------------------------------------------|
| Voltage: | 110 - 240 V AC 50 / 60 Hz |
| Dimensions: | 88 x 88 x 42 mm (92141) |
| Power consumption: | approx. 0.2 W |
| Detection area: | horizontal 180° (Wall mounting) max. 10 m across |
| Range: | max. 3 m towards |
| Monitored area (tangential movement): | 150 m ² / 1.1 m mounting height |
| Mounting height min./max./recommended: | 1 m / 2.2 m / 1.1 m |
| Degree / class of protection: | IP54 (92141) |
| Impact strength: | IK05 |
| Ambient temperature: | -25 °C to +50 °C |
| Housing: | polycarbonate, UV-resistant |
| Material color: | pure white mat, similar to RAL9010 (92139) |
| Pulse interval: | 2 or 9 sec |

Product information

Set : Indoor 180-S covering not included + Frame
IP54 Indoor 180 pure white mat, similar to RAL9010
+ Surface mounting socket Indoor 180 pure white
mat, similar to RAL9010

Slave device

For extending the detection area of a Master device

Compatible with 230 V devices. Concerning exceptions please
see the respective master device.

Available with covering (centre plate dimensions 60 x 60 mm)
or without covering for use with covering (centre plate
dimensions 50 x 50 mm) in 5 different colours

In combination with centre plates usable with current frame
systems of various manufacturers

B.E.G. frames and centre plates for combination with other
frame systems available



Set items

To receive the bundle according to the technical specification, please order the items listed.



Indoor 180-S covering not included
Art.No: 92660

Voltage: 110 – 240 V AC 50 / 60 Hz
Dimensions: covering not included 70 x 70 x 61 mm
Power consumption: approx. 0.2 W



Frame IP54 Indoor 180
Art.No: 92139

Dimensions: 87 x 87 mm
Degree / class of protection: IP54
Housing: polycarbonate, UV-resistant



Surface mounting socket Indoor 180
Art.No: 92141

Dimensions: 88 x 88 x 42 mm
Degree / class of protection: IP54
Impact strength: IK05