

**B.E.G.****LUXOMAT®**

## Indoor 180-S covering not included Set 92660-92630-92141

Slave PIR wall-mounted motion detector with 180° detection angle and a range of up to 10 m (150 m<sup>2</sup>), for expanding the detection zone

### Order data

| Designation                        | Colour     | Art.No |
|------------------------------------|------------|--------|
| Indoor 180-S covering not included | -          | 92660  |
| Frame IP20 Indoor 180              | pure white | 92630  |
| Surface mounting socket Indoor 180 | pure white | 92141  |

## Technical data

|   |   |
|---|---|
| Voltage:                                  | 110 - 240 V AC<br>50 / 60 Hz                                  |
| Dimensions:                               | <b>88 x 88 x 42<br/>mm (92141)</b>                            |
| Power consumption:                        | approx. 0.2 W   |
| Detection area:                           | horizontal 180°<br>(Wall mounting)<br>max. 10 m<br>across     |
| Range:                                    | max. 3 m<br>towards   |
| Monitored area (tangential movement):     | 150 m <sup>2</sup> / 1.1 m<br>mounting<br>height              |
| Mounting height<br>min./max./recommended: | 1 m / 2.2 m /<br>1.1 m  |
| Degree / class of<br>protection:          | <b>IP54 (92141)</b>   |
| Impact strength:                          | IK05  |
| Ambient temperature:                      | -25 °C to +50<br>°C   |
| Housing:                                  | polycarbonate,<br>UV-resistant                                |
| Material color:                           | <b>pure white<br/>mat, similar<br/>to RAL9010<br/>(92630)</b> |
| Pulse interval:                           | 2 or 9 sec  |

## Product information

Set : Indoor 180-S covering not included + Frame  
IP20 Indoor 180 pure white mat, similar to RAL9010  
+ Surface mounting socket Indoor 180 pure white  
mat, similar to RAL9010

Slave device

For extending the detection area of a Master device

Compatible with 230 V devices. Concerning exceptions please  
see the respective master device.

Available with covering (centre plate dimensions 60 x 60 mm)  
or without covering for use with covering (centre plate  
dimensions 50 x 50 mm) in 5 different colours

In combination with centre plates usable with current frame  
systems of various manufacturers

B.E.G. frames and centre plates for combination with other  
frame systems available




## Set items

To receive the bundle according to the technical specification, please order the items listed.



**Indoor 180-S covering not included**  
Art.No: 92660

Voltage: 110 – 240 V AC 50 / 60 Hz  
Dimensions: covering not included 70 x 70 x 61 mm  
Power consumption: approx. 0.2 W



**Frame IP20 Indoor 180**  
Art.No: 92630

Dimensions: 86 x 86 mm  
Degree / class of protection: IP20  
Housing: polycarbonate, UV-resistant



**Surface mounting socket Indoor 180**  
Art.No: 92141

Dimensions: 88 x 88 x 42 mm  
Degree / class of protection: IP54  
Impact strength: IK05