

B.E.G.**LUXOMAT®**

Indoor 180-TR covering not included Set 92668-92139

230V PIR wall-mounted motion detector with 180° detection angle and a range of up to 10 m (150 m²), featuring an acoustic sensor for staircase lighting control

Order data

Designation	Colour	Art.No
Indoor 180-TR covering not included	-	92668
Frame IP54 Indoor 180	pure white	92139

Technical data

Voltage:	110 - 240 V AC 50 / 60 Hz Power supply via staircase switch
Dimensions:	covering not included 70 x 70 x 61 mm + 87 x 87 mm (92139)
Power consumption:	approx. 0.8 W
Detection area:	horizontal 180° (Wall mounting) max. 10 m across max. 3 m towards
Range:	150 m ² / 1.1 m mounting height
Monitored area (tangential movement):	1 m / 2.2 m / 1.1 m
Mounting height min./max./recommended:	IP20 / Class II + IP54 (92139)
Degree / class of protection:	IK05
Impact strength:	-25 °C to +50 °C
Ambient temperature:	polycarbonate, UV-resistant
Housing:	pure white mat, similar to RAL9010 (92139)
Material color:	
Channel 1	
Switching power:	0.2 A / 230 V Pulse duration: 0.1 s;
Follow-up time:	Deactivation of light evaluation 1 min - 10 min
Switch-on threshold:	2 - 2000 Lux

Product information

Set : Indoor 180-TR covering not included + Frame
IP54 Indoor 180 pure white mat, similar to RAL9010

Wall motion detector designed for stair light timer switches

Triac version with 2-wire technology, no neutral

Guarantees correct operation with the SCT1 (max. 10 sensors
per unit)

Available with covering (centre plate dimensions 60 x 60 mm)
or without covering for use with covering (centre plate
dimensions 50 x 50 mm) in 5 different colours

In combination with centre plates usable with current frame
systems of various manufacturers

B.E.G. frames and centre plates for combination with other
frame systems available



Set items

To receive the bundle according to the technical specification, please order the items listed.



Indoor 180-TR covering not included

Art.No: 92668

Voltage: 110 – 240 V AC 50 / 60 Hz Power supply via staircase switch

Dimensions: covering not included 70 x 70 x 61 mm

Power consumption: approx. 0.8 W



Frame IP54 Indoor 180

Art.No: 92139

Dimensions: 87 x 87 mm

Degree / class of protection: IP54

Housing: polycarbonate, UV-resistant