

B.E.G.**LUXOMAT[®]net**

KNX Control Touch-Panel

Prod.No. 90120 EAN: 4007529901203

- Voltage: 230 V AC 50 / 60 Hz
- Dimensions: 195 x 155 x 4 mm
- Power consumption: 11 W

Order data

Designation	Colour	Art.No
KNX Control Touch-Panel		90120

Technical data

Voltage:	230 V AC 50 / 60 Hz
Dimensions:	195 x 155 x 4 mm
Power consumption:	11 W
Degree / class of protection:	IP20 / Class I
Ambient temperature:	0 °C to +45 °C
Housing:	Plastic ABS Terez 32/19V0
Material color:	-
Display elements:	LED red for displaying normal/addressing mode Graphic-compatible 5.7" TFT colour display 320 x 240 pixels with LED background illumination
Manual operation:	Learn key for switching normal/addressing mode
KNX TP 256:	Yes
Connections and wires:	3x 1.5 mm ² (power supply) Bus line: EIB/KNX bus terminal (black/red) USB socket type Mini-B

Product information

Graphic-compatible TFT colour display with LED background lighting

All important standard functions and status displays of the KNX system

Password protection, logic module, alarm module, etc.

Password assignment for 10 main operator pages and all configuration pages possible

Individual symbol assignment

110 KNX functions in the form of operator pages

Up to 64 easy to configure scenarios

Easy operation

Integrated weekly switching schedule

Occupancy simulation

Logical linking of up to 60 objects

