



KNX SBA-4C-230V

Prod.No. 90190 EAN: 4007529901906

- Voltage: 230 V AC 50 Hz
- Dimensions: 86 x 72 x 60 mm (4 TE)
- Output voltage: 230 V AC 50 Hz

Order data

Designation	Colour	Art.No
KNX SBA-4C-230V		90190

Technical data

Voltage:	230 V AC 50 Hz
Dimensions:	86 x 72 x 60 mm (4 TE)
Output voltage:	230 V AC 50 Hz
Degree / class of protection:	IP20 / Class II
Ambient temperature:	0 °C to +45 °C
Housing:	Plastic LEXAN UL-94-V0
Material color:	white
Display elements:	Red LED: Programming LED Green LED: Channel status
Manual operation:	Manual operation of the shutter channels directly on the device
KNX TP 256:	Yes
Switching power:	600 VA, $\cos \varphi = \text{null}$ Roller blind motors

Product information

The blind actuators KNX SBA-4C-230 V and KNX SBA-8C-230 V receive KNX telegrams and control several blind motors with limit switches independently of one another

Each channel is controlled with two monostable relays and can also be manually activated with the buttons at the actuator

Each channel can be individually programmed through the ETS3/4. Status reports, blocking functions, central switch functions and extensive calibration and positioning functions are available for selection

In the event of bus voltage failure or resumption, the switch positions of the relay can be individually programmed for each channel

The device is planned for permanent installation on a DIN-rail (top-hat) in high voltage current distributors

Installation must take place in dry interiors



