

**B.E.G.****LUXOMAT<sup>®</sup>net**

## KNXnet/IP Interface

Prod.No. 90125 EAN: 4007529901258

Cost-efficient programming of a KNX system via LAN

Programming interfaces from the ETS to the KNX BUS

Scan function (ETS3 and 4)

### Order data

Designation	Colour	Art.No
KNXnet/IP Interface		90125

## Technical data

Voltage:	12 - 30 V AC / DC
Dimensions:	86 x 72 x 58 mm (4 TE)
Degree / class of protection:	IP20 / Class I
Ambient temperature:	0 °C to +45 °C
Housing:	Plastic LEXAN UL-94-V0
Material color:	white
Display elements:	LA-LED: for indicating communication on the Ethernet connection, LK-LED: for indicating Ethernet connection
Manual operation:	Learn keys for switching normal/addressing mode
KNX TP 256:	Yes
Connections and wires:	Bus line: EIB/KNX bus terminal (black/red), Bus terminal yellow/white (power supply), RJ45 socket (ethernet)

## Product information

Cost-efficient programming of a KNX system via LAN

Programming interfaces from the ETS to the KNX BUS

Scan function (ETS3 and 4)

KNXnet/IP-secured tunnel connection

Plastic housing, 4 widths units (DIN-rail, top hat)

Connection: 12-30V AC/DC, network and KNX



