

**B.E.G.**

**LUXOMAT<sup>®</sup> net**



## LAN-IF/KNXs REG

Prod.No. 90404 EAN: 4007529904044

- Voltage: via KNX BUS
- Dimensions: 90 x 18 x 60 mm (1 TE)
- Typ. power input: 20 mA

### Order data

Designation	Colour	Art.No
LAN-IF/KNXs REG	-	90404

## Technical data

Voltage:	via KNX BUS
Dimensions:	90 x 18 x 60 mm (1 TE)
Typ. power input:	20 mA
Degree / class of protection:	IP20 / Class III
Ambient temperature:	-5 °C to +45 °C
Housing:	polycarbonate, UV-resistant (PC)
Material color:	-
KNX TP 256:	Yes
KNX Secure:	Yes
Connections and wires:	1 x KNX bus terminal black/red, 1 x RJ45 socket (ethernet)

## Product information

The LAN-IF/KNXs REG serves as a secure interface between a LAN (IP, Ethernet) and KNX

Can be used as programming interface for the ETS

As KNX Secure Interface (tunneling) the device prevents unauthorized access to the system

Up to 8 connections simultaneously

The security option can be activated or deactivated in the ETS.

The LEDs indicate operating conditions as well as communication errors on the KNX bus



