LAN-IF/KNXs REG

Prod.No. 90404 EAN: 4007529904044

- Voltage: via KNX BUS
- Dimensions: 90 x 18 x 60 mm (1 TE)
- Typ. power input: 20 mA

Order data

Designation	Colour	Art.No
LAN-IF/KNXs REG	-	90404

Technical data

Voltage:	via KNX BUS
Dimensions:	90 x 18 x 60 mm (1 TE)
Typ. power input:	20 mA
Degree / class of protection:	IP20 / Class III
Ambient temperature:	-5 °C to +45 °C
Housing:	polycarbonate, UV-resistant (PC)
Material color:	-
KNX TP 256:	Yes
KNX Secure:	Yes
Connections and wires:	1 x KNX bus terminal black/red, 1 x RJ45 socket (ethernet)

Product information

The LAN-IF/KNXs REG serves as a secure interface between a LAN (IP, Ethernet) and KNX

Can be used as programming interface for the ETS

As KNX Secure Interface (tunneling) the device prevents unauthorized access to the system

Up to 8 connections simultaneously

The security option can be activated or deactivated in the ETS.

The LEDs indicate operating conditions as well as communication errors on the KNX bus

18

55

44

90

7

45

67

24

53

+ −

KNX

- +
KNX

ETHERNET

beg-luxomat.com 03.02.2026