

**B.E.G.****LUXOMAT<sup>®</sup> net**

## LK-TP/KNXs REG

Prod.No. 90410 EAN: 4007529904105

KNX TP Line coupler in a compact design. It connects two KNX bus segments via twisted pair

KNX Secure ready

extended filter table for main group 0 to 31

### Order data

Designation	Colour	Art.No
LK-TP/KNXs REG	-	90410

## Technical data

Voltage:	via KNX BUS
Dimensions:	90 x 18 x 55 mm (1 TE)
Typ. power input:	10 mA typical
Degree / class of protection:	IP20 / Class III
Ambient temperature:	-5 °C to +45 °C
Housing:	polycarbonate, UV-resistant (PC)
Material color:	-
KNX TP 256:	Yes
KNX Secure:	Yes
Connections and wires:	2 x KNX bus terminal black/red

## Product information

KNX TP Line coupler in a compact design. It connects two KNX bus segments via twisted pair

KNX Secure ready

extended filter table for main group 0 to 31

ensures a galvanic isolation between the lines

Supports KNX long frames

Buffer for up to 2 x 50 telegrams

Security proxy and segment coupler function

The buttons on the front panel allow disabling the telegram filter for testing purposes

LEDs to indicate operating conditions as well as errors



