

**B.E.G.****LUXOMAT® net**

## PBM-KNX-DX-4W

Prod.No. 93365 EAN: 4007529933655

- Voltage: via KNX BUS
- Dimensions: 38 x 41 x 12 mm
- Typ. power input: 9.5 mA (typ.) (I<sub>max</sub> parameterisable 12.5 mA or 20 mA)

### Order data

| Designation   | Colour | Art.No |
|---------------|--------|--------|
| PBM-KNX-DX-4W |        | 93365  |

## Technical data

|                               |   |
|-------------------------------|---|
| Voltage:                      | via KNX BUS   |
| Dimensions:                   | 38 x 41 x 12 mm   |
| Typ. power input:             | 9.5 mA (typ.) (I <sub>max</sub> parameterisable 12.5 mA or 20 mA)                       |
| Degree / class of protection: | IP20 / Class III  |
| Ambient temperature:          | -5 °C to +45 °C   |
| Display elements:             | Programming LED   |
| KNX TP 256:                   | Yes   |
| Connections and wires:        | plug board: 8 pin<br>Prefabricated connecting wires (extendable to a total of max. 5 m) |
| LED connector:                | I <sub>max</sub> 3.6 mA const.<br>(PWM) LED 3.5 V / 4 mA                                |

## Product information

Binary input or output device (push button interface) for pattress boxes (60 mm)

There are four channels available. Each can either be used as input for a potential-free push-button or switch contact or as binary output for switching a control lamp.

User-friendly ETS interface

The following functions are possible:

- Switching
- Forced operation
- Percentage
- Sequencer
- HVAC mode
- Dimming
- Blinds control
- Scene
- Edge function
- Counter

Settings ex ETS 4 for integration in KNX systems

The product database for import into the ETS database can be downloaded from the B.E.G. homepage.



