

B.E.G.**LUXOMAT®**

PD4-M-3C-TRIO-SM Set 92740-92467

Occupancy detector particularly for classrooms and training classrooms

Two contacts, one of them dry, for two groups of light, separate switching possible

One potential-free contact for blackboard illumination or HVAC

Areas of application

- open-plan offices
- conference rooms
- classrooms/seminar rooms

Order data

Designation	Colour	Art.No
PD4-M-3C-TRIO-SM	white	92740
Wire basket BSK (Ø 164 x 143 mm)	white	92467

Technical data

Voltage:	110 - 240 V AC 50 / 60 Hz
Dimensions:	Ø 164 x 143 mm (92467)
Power consumption:	approx. 0.5 W
Detection area:	horizontal 360° (Ceiling mounting) max. Ø 24 m across max. Ø 8 m towards max. Ø 6.4 m seated
Range:	
Monitored area (tangential movement):	450 m ² / 2.5 m mounting height
Mounting height min./max./recommended:	2 m / 10 m / 2.5 m
Degree / class of protection:	IP20 / Class II
Impact strength:	IK09 (92467)
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant + coated steel basket (92467) white mat, similar to RAL9010
Material color:	

Channel 1 (lighting control)

Switching power:	3000 W, $\cos \varphi = 1$ 1500 VA, $\cos \varphi = 0.5$ 800 W LED max. inrush current I_p (20 ms) = 165 A max. inrush current I_p (200 μ s) = 800 A
Type of contact (k):	1x μ -contact, NO contact with tungsten pre-make contact
Switch-on threshold:	10 - 2000 Lux

Channel 2 (lighting control potential-free (dry))

Switching power:	3000 W, $\cos \varphi = 1$ 1500 VA, $\cos \varphi = 0.5$ 800 W LED max. inrush current I_p (20 ms) = 165 A, I_p (200 μ s) = 800 A
Switch-on threshold:	10 - 2000 Lux

Product information

Set : PD4-M-3C-TRIO-SM + Wire basket BSK (Ø 164 x 143 mm) white

Occupancy detector particularly for classrooms and training classrooms

Two contacts, one of them dry, for two groups of light, separate switching possible

One potential-free contact for blackboard illumination or HVAC

One common detection area

Two independent, movable light sensors

Manual switching possible via two or three pushbuttons

Version as master device

Detection area can be extended by using slave devices

Additional functions can be set up using the optional remote control.

Relay with tungsten pre-make contact, optimised for LED loads

Type of contact: 1x μ -contact, dry
NO contact with tungsten pre-make contact

Channel 3 (HVAC control or lighting control, potential-free (dry))




Switching power: 3000 W, $\cos \varphi = 1$
1500 VA, $\cos \varphi = 0.5$
800 W LED
max. inrush current I_p (20ms) = 120 A

Type of contact: 1x μ -contact, dry
NO contact

Channel 1 to channel 3

Follow-up time: 1 min - 90 min

Light measuring: Mixed light measuring



Set items

To receive the bundle according to the technical specification, please order the items listed.



PD4-M-3C-TRIO-SM

Art.No: 92740

Voltage: 110 – 240 V AC 50 / 60 Hz

Dimensions: Ø 124 x 85 mm

Power consumption: approx. 0.5 W



Wire basket BSK (Ø 164 x 143 mm)

Art.No: 92467

Dimensions: Ø 164 x 143 mm

Impact strength: IK09

Housing: coated steel basket