

**B.E.G.**

**LUXOMAT®**



## PD4-M-HCL2-SM DALI-2 Set 93485-92386

- Voltage: 230 V AC  $\pm$ 10% 50 Hz
- Dimensions:  $\varnothing$  124 x 85 mm
- Power consumption: approx. 2 W

### Order data

Designation	Colour	Art.No
PD4-M-HCL2-SM DALI-2	white	93485
Socket IP54 PD4-TRIO-SM	white	92386

## Technical data

Voltage:	230 V AC $\pm$ 10% 50 Hz
Dimensions:	Ø 124 x 85 mm
Power consumption:	approx. 2 W
Detection area:	horizontal 360° (Ceiling mounting) max. Ø 24 m across
Range:	max. Ø 8 m towards max. Ø 6.4 m seated
Monitored area (tangential movement):	450 m <sup>2</sup> / 2.5 m mounting height
Mounting height min./max./recommended:	2 m / 10 m / 2.5 m
Degree / class of protection:	<b>IP54 (92386)</b>
Impact strength:	IK04
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant
Material color:	white, similar to RAL9010

### DALI Control

DALI output:	100 mA (guaranteed), 120 mA (max.)
Supported control gear:	DT5, DT6, DT7, DT8-Tc (HCL only possible with DT8-Tc, 2700 - 6500 K)
Supported control devices:	B.E.G. BMS (motion detection)
Follow-up time:	1 min - 150 min
Orientation light:	5 - 100 % / OFF / 1 min - 255 min / $\infty$
Brightness set value:	10 - 2500 Lux

### Relay (dry NO)

Switching power:	2300 W, $\cos \varphi$ = 1 1150 VA, $\cos \varphi$ = 0.5 800 W LED max. inrush current $I_p$ (20 ms) = 165 A, $I_p$ (200 $\mu$ s) = 800 A
Type of contact:	1x $\mu$ -contact, NO contact
Follow-up time:	5 sec - 120 min (HVAC)

## Product information

Set : PD4-M-HCL2-SM DALI-2 + Socket IP54 PD4-  
TRIO-SM white



## Set items

To receive the bundle according to the technical specification, please order the items listed.



**PD4-M-HCL2-SM DALI-2**  
Art.No: 93485

Voltage: 230 V AC  $\pm 10\%$  50 Hz  
Dimensions:  $\varnothing$  124 x 85 mm  
Power consumption: approx. 2 W



**Socket IP54 PD4-TRIO-SM**  
Art.No: 92386

Degree / class of protection: IP54  
Housing: polycarbonate, UV-resistant  
Material color: white