



PD4-S-GH-SM

Prod.No. 92265 EAN: 4007529922659

■ Voltage: 110 - 240 V AC 50 / 60 Hz

■ Dimensions: Ø 101 x 76 mm

■ Power consumption: approx. 0.2 W

Order data

| Designation | Colour | Art.No |
|-------------|--------|--------|
| PD4-S-GH-SM | white | 92265 |

Accessories

| Designation | Colour | Art.No |
|--|-------------|--------|
| Surface mounting socket IP65 PD4- SM IP54 | white | 92376 |
| Wire basket BSK (Ø 200 x 90 mm) | white | 92199 |
| Blinds PD4 | transparent | 92313 |
| Pendulum mounting set PD2/3/4 SM | white | 93179 |

Technical data

Degree / class of

Pulse interval:

Power consumption: approx. 0.2 W

horizontal 360° Detection area: oval (Ceiling

mounting)

Range: $30 \text{ m} \times 19 \text{ m}$ Monitored area (tangential $440 \text{ m}^2 / 14 \text{ m}$

movement):

mounting
height

Mounting height 5 m / 16 m / 14 min./max./recommended: m

protection: IP54 / Class II
Impact strength: IK04

Impact strength: IK04

-25 °C to +50

Ambient temperature:

Housing: polycarbonate,

UV-resistant

2 or 9 sec

white mat,
Material color: similar to
RAL9010

Product information

Slave device for high-bay applications

For extending the detection area of a Master device

Trigger pulse to master device upon detected movement independent of the ambient light level


Compatible with 230 V devices. Concerning exceptions please see the respective master device.


There are markings to ensure correct alignment during installation


When used in high-bay warehouses, care should be taken that, in the cross-aisles of the warehouse, detectors are installed that can detect movement only in the desired aisle locations, by using blinds or other technical arrangements.


Application examples:

high-bay warehouse









Accessories



Surface mounting socket IP65 PD4-SM IP54

Art.No: 92376

Dimensions: Ø 115 x 70 mm Degree / class of protection: IP65 Impact strength: IK07



Wire basket BSK (Ø 200 x 90 mm)

Art.No: 92199

Dimensions: Ø 200 x 90 mm Impact strength: IK09 Housing: coated steel basket



Blinds PD4 Art.No: 92313

Housing: Housing UV- and shockresistant Polycarbonate Material color: transparent



Pendulum mounting set PD2/3/4 SM

Art.No: 93179

Dimensions: 1: Ø 113 x 79 mm, 2: Ø 113

x 34 mm

Housing: polycarbonate, UV-resistant Material color: white, similar to RAL9010