

**B.E.G.****LUXOMAT®**

## PD4N-1C-C-SM

Prod.No. 92270 EAN: 4007529922703

- Voltage: 110 – 240 V AC 50 / 60 Hz
- Dimensions: Ø 109 x 65 mm
- Power consumption: approx. 0.4 W

### Areas of application

- corridors/hallways

### Order data

Designation	Colour	Art.No
PD4N-1C-C-SM	white	92270

### Accessories

Designation	Colour	Art.No
RC-Arc extinction kit	white	10880
Mini-RC-Arc extinction kit		10882
BLE-IR-Adapter	black	93067
IR-Adapter for Smartphones	black	92726
IR-PD3N	-	92105
IR-PD3/4N-1C-E	-	93110
IR-PD-Mini	-	92159
Wire basket BSK (Ø 200 x 90 mm)	white	92199
Wall holder PD4-SM	white	92441
Pendulum mounting set PD2/3/4 SM	white	93179

## Technical data

Voltage:	110 – 240 V AC 50 / 60 Hz
Dimensions:	Ø 109 x 65 mm
Power consumption:	approx. 0.4 W
Detection area:	horizontal 360° (Ceiling mounting) max. Ø 40 m across
Range:	max. Ø 20 m towards
Monitored area (tangential movement):	250 m² / 2.5 m mounting height
Mounting height min./max./recommended:	2.4 m / 2.6 m / 2.5 m
Degree / class of protection:	IP44 / Class II
Impact strength:	IK04
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant
Material color:	white mat, similar to RAL9010

### Channel 1 (lighting control)

Switching power:	2300 W, $\cos \varphi$ = 1 1150 VA, $\cos \varphi$ = 0.5 800 W LED max. inrush current $I_p$ (20 ms) = 165 A max. inrush current $I_p$ (200 µs) = 800 A
Type of contact (k):	1x µ-contact, NO contact with tungsten pre- make contact
Follow-up time:	15 sec – 30 min, Pulse
Switch-on threshold:	10 – 2000 Lux

## Product information

Remote control-capable ceiling motion detector designed for corridors

One channel for light switching

Zero crossing switching

Special optical system for detection of even the smallest movements

Additional functions can be set up using the optional remote control.

Uninterrupted parallel circuit detection of several detectors

Manual switching via push-button possible

Factory settings 10 min and 500 lux

There are markings to ensure correct alignment during installation

### Application examples:

corridors/hallways



## Accessories



### RC-Arc extinction kit

Art.No: 10880

Voltage: 230 V AC ±10%  
 Dimensions: 38 x 12 x 26 mm  
 Degree / class of protection: IP20 /  
 Class II



### Mini-RC-Arc extinction kit

Art.No: 10882

Voltage: 230 V AC ±10%  
 Dimensions: 50 x 23 x 8 mm  
 Degree / class of protection: IP20 /  
 Class II



### BLE-IR-Adapter

Art.No: 93067

Dimensions: 40 x 55 x 103 mm  
 Material color: black  
 Frequency: 2.4 GHz ISM band, GFSK  
 0.2 dBm + 5.3 dBi = 5.5 dBm



### IR-Adapter for Smartphones

Art.No: 92726

Dimensions: 47 x 19 x 10 mm  
 Degree / class of protection: IP20  
 Ambient temperature: -20 °C to +40 °C



### IR-PD3N

Art.No: 92105

Battery: 3.0 V Lithium CR2032  
 (inclusive)  
 Dimensions: 80 x 60 x 8 mm  
 Material color: -



### IR-PD3/4N-1C-E

Art.No: 93110


Battery: 3.0 V Lithium CR2032  
 (inclusive)  
 Dimensions: 80 x 60 x 8 mm  
 Material color: -



### IR-PD-Mini

Art.No: 92159

Battery: 3.0 V Lithium CR2032  
 (inclusive)  
 Dimensions: 57 x 35 x 7 mm  
 Material color: -



### Wire basket BSK (Ø 200 x 90 mm)

Art.No: 92199

Dimensions: Ø 200 x 90 mm  
 Impact strength: IK09  
 Housing: coated steel basket



### Wall holder PD4-SM

Art.No: 92441

Dimensions: 130 x 100 x 53 mm  
 Housing: polycarbonate, UV-resistant  
 Material color: white



**Pendulum mounting set PD2/3/4 SM**

Art.No: 93179

Dimensions: 1 : Ø 113 x 79 mm, 2 : Ø 113  
x 34 mm

Housing: polycarbonate, UV-resistant

Material color: white, similar to RAL9010