



## PD4N-CAS DALI-2 Set 93473-93465-93073

CASAMBI-compatible PIR motion sensor with built-in DALI-2 bus power supply, 360° detection, and a range of up to Ø24m (450 m<sup>2</sup>)

### Order data

Designation	Colour	Art.No
PD4N-CAS DALI-2	white	93473
SM socle mounting set IP54 PD4N H	white	93465
Corridor lens PD4N type A	white	93073

## Technical data

Voltage:	230 V AC ±10% 50 Hz
Dimensions:	<b>Ø 106 x 95 mm + Ø 110 x 45 mm (93465)</b>
Settings:	Casambi App
Power consumption:	0.5 W
Detection area:	<b>horizontal 360° (Ceiling mounting) (93073)</b> <b>max. Ø 40 m across</b> <b>max. Ø 20 m towards (93073)</b> <b>250 m² / 2.5 m mounting height (93073)</b>
Range:	<b>2.4 m / 2.6 m / 2.5 m (93073)</b>
Monitored area (tangential movement):	<b>IP54 (93465)</b>
Mounting height min./max./recommended:	<b>IK04</b>
Degree / class of protection:	<b>-5 °C to +45 °C</b>
Impact strength:	polycarbonate, UV-resistant
Ambient temperature:	<b>white, similar to RAL9010 (93073)</b>
Housing:	4
Material color:	<b>Channel 1 (lighting control)</b>
Number of PIR sensors:	80 mA (guaranteed), 125 mA (max.), shut down mechanism
DALI output:	DT0, DT5, DT6, DT7, DT8
Supported control gear:	- (single master)
Supported control devices:	1 sec – 60 min
Follow-up time:	1 – 4000 Lux
Brightness set value:	Mixed light measuring
Light measuring:	

## Product information

Set : PD4N-CAS DALI-2 + SM socle mounting set IP54 PD4N H white, similar to RAL9010 + Corridor lens PD4N type A white, similar to RAL9010

Casambi-enabled occupancy detector

DALI-2 interface for controlling digital dimmable ECGs in broadcast/multicast mode

Integrated temperature monitoring and short-circuit detection

Version as single-master device, can be networked wirelessly

DALI output power can be increased with accessories

Bright LED indication for commissioning

Mixed light measurement with internal and external light sensor

Weighting between internal and external light sensor can be adapted to suit the application

Adjustment of the reflection factor and input of the luminosity for the display of the actual luminosity in the app

Extension of the detection area with additional B.E.G. Casambi devices possible

Individual adaption of detection sensitivity for each PIR sensor

Detection area can be restricted with blinds

Functions adjustable via Casambi app

Including pre-assembled spring clamp with strain relief and contact protection cap for recessed ceiling mounting

Accessory for surface mounting available

Accessories for wall mounting optionally available

Further accessories for colour matching optionally available



# CASAMBI



## Set items

To receive the bundle according to the technical specification, please order the items listed.



### PD4N-CAS DALI-2

Art.No: 93473

Voltage: 230 V AC  $\pm 10\%$  50 Hz  
Dimensions:  $\varnothing$  106 x 95 mm  
Settings: Casambi App



### SM socle mounting set IP54 PD4N H

Art.No: 93465

Dimensions:  $\varnothing$  110 x 45 mm  
Degree / class of protection: IP54  
Material color: white, similar to  
RAL9010



### Corridor lens PD4N type A

Art.No: 93073

Detection area: horizontal 360° (Ceiling  
mounting)  
Range: max.  $\varnothing$  40 m across  
max.  $\varnothing$  20 m towards  
Monitored area (tangential movement): 250  
m<sup>2</sup> / 2.5 m mounting height