



## PD4N-CAS DALI-2 Set 93473-93787

CASAMBI-compatible PIR motion sensor with built-in DALI-2 bus power supply, 360° detection, and a range of up to Ø24m (450 m<sup>2</sup>)

### Order data

| Designation                       | Colour        | Art.No |
|-----------------------------------|---------------|--------|
| PD4N-CAS DALI-2                   | white         | 93473  |
| SM socle mounting set IP54 PD4N H | traffic white | 93787  |

## Technical data

|   |   |
|---|---|
| Voltage:                                  | 230 V AC ±10%<br>50 Hz  |
| Dimensions:                               | <b>Ø 106 x 95<br/>mm + Ø 110 x<br/>45 mm<br/>(93787)</b>  |
| Settings:                                 | Casambi App   |
| Power consumption:                        | 0.5 W   |
| Detection area:                           | horizontal 360°<br>oval (Ceiling<br>mounting)<br>max. Ø 24 m<br>across<br>max. Ø 8 m<br>towards<br>max. Ø 6.4 m<br>seated |
| Range:                                    | 450 m <sup>2</sup> / 2.5 m<br>mounting<br>height  |
| Monitored area (tangential<br>movement):  | 2 m / 10 m / 2.5<br>m   |
| Mounting height<br>min./max./recommended: |   |
| Degree / class of<br>protection:          | <b>IP54 (93787)</b>   |
| Impact strength:                          | IK04  |
| Ambient temperature:                      | -5 °C to +45 °C   |
| Housing:                                  | polycarbonate,<br>UV-resistant<br><b>traffic white,<br/>similar to<br/>RAL9016<br/>(93787)</b>                            |
| Material color:                           |   |
| Number of PIR sensors:                    | 4   |
| <b>Channel 1 (lighting<br/>control)</b>   |   |
| DALI output:                              | 80 mA<br>(guaranteed),<br>125 mA (max.),<br>shut down<br>mechanism  |
| Supported control gear:                   | DT0, DT5, DT6,<br>DT7, DT8  |
| Supported control devices:                | - (single<br>master)  |
| Follow-up time:                           | 1 sec - 60 min  |
| Brightness set value:                     | 1 - 4000 Lux  |
| Light measuring:                          | Mixed light<br>measuring  |

## Product information

Set : PD4N-CAS DALI-2 + SM socle mounting set IP54  
PD4N H traffic white, similar to RAL9016

Casambi-enabled occupancy detector

DALI-2 interface for controlling digital dimmable ECGs in  
broadcast/multicast mode

Integrated temperature monitoring and short-circuit detection

Version as single-master device, can be networked wirelessly

DALI output power can be increased with accessories

Bright LED indication for commissioning

Mixed light measurement with internal and external light  
sensor

Weighting between internal and external light sensor can be  
adapted to suit the application

Adjustment of the reflection factor and input of the luminosity  
for the display of the actual luminosity in the app

Extension of the detection area with additional B.E.G. Casambi  
devices possible

Individual adaption of detection sensitivity for each PIR sensor

Detection area can be restricted with blinds

Functions adjustable via Casambi app

Including pre-assembled spring clamp with strain relief and  
contact protection cap for recessed ceiling mounting

Accessory for surface mounting available

Accessories for wall mounting optionally available

Further accessories for colour matching optionally available



# CASAMBI



## Set items

To receive the bundle according to the technical specification, please order the items listed.



### **PD4N-CAS DALI-2**

Art.No: 93473

Voltage: 230 V AC  $\pm 10\%$  50 Hz

Dimensions:  $\varnothing$  106 x 95 mm

Settings: Casambi App



### **SM socle mounting set IP54 PD4N H**

Art.No: 93787

Dimensions:  $\varnothing$  110 x 45 mm

Degree / class of protection: IP54

Material color: traffic white, similar to RAL9016