



PD4N-DALI-SYS Set 93340-93741-92199

Wide motion detection range DALI multisensor

Powered via DALI bus

Seamless integration in B.E.G. LUXOMAT® net
DALI-SYS

Order data

| Designation | Colour | Art.No |
|--|------------|--------|
| PD4N-DALI-SYS | white | 93340 |
| Corridor lens PD4N type A, Cover ring | anthracite | 93741 |
| Wire basket BSK (Ø 200 x 90 mm) | white | 92199 |

Technical data

| | |
|---|---|
| Voltage: | via DALI Bus, max. 22.5 V DC |
| Dimensions: | Ø 200 x 90 mm (92199) |
| Settings: | B.E.G. DALI-SYS ROUTER / B.E.G. DALI-SYS PC- Tools |
| Typ. power input: | 7 mA |
| Detection area: | horizontal 360° (Ceiling mounting) (93741) max. Ø 40 m across max. Ø 20 m towards (93741) |
| Range: | 250 m² / 2.5 m mounting height (93741) |
| Monitored area (tangential movement): | 2.4 m / 2.6 m / 2.5 m (93741) |
| Mounting height min./max./recommended: | |
| Degree / class of protection: | IP20 / Class II |
| Impact strength: | IK09 (92199) |
| Ambient temperature: | -25 °C to +55 °C |
| Housing: | polycarbonate, UV-resistant + coated steel basket (92199) anthracite mat, similar to RAL7016 (93741) |
| Material color: | |
| Follow-up time: | 1 sec - 120 min |
| Orientation light: | 5 - 100 % / 1 min - 120 min / ∞ |
| Brightness set value: | 10 - 2500 Lux |
| Light measuring: | Mixed light measuring |

Product information

Set : PD4N-DALI-SYS + Corridor lens PD4N type A,
Cover ring anthracite mat, similar to RAL7016 + Wire
basket BSK (Ø 200 x 90 mm) white

Wide motion detection range DALI multisensor

Powered via DALI bus

Seamless integration in B.E.G. LUXOMAT® net DALI-SYS

Bright LED indication for commissioning

Detection area can be extended thanks to master-slave-mode

Mixed light measurement with internal and external light
sensor

Semi-automatic, full-automatic or twilight switch mode

Integrated daylight harvesting circuit (or switch output)

Guided Light, Soft-Start PLUS, Orientation light PLUS

Works out-of-the box for easy installation check

Full range of functions can only be activated with other
products of the product group B.E.G. LUXOMAT® net DALI-SYS

Suitable for mounting in false ceilings and flush-mounting

Accessory for surface mounting available

This article is a component of a lighting control system from
B.E.G., which supports the use of DALI control gear
(luminaires, relays) from other manufacturers

The use of DALI application controllers from other
manufacturers is not supported

The use of DALI input devices (sensors, push-buttons) from
other manufacturers is not supported

Additional system components (hardware) from B.E.G. are
required

Additional services (planning, commissioning and
maintenance) from B.E.G. are required



Set items

To receive the bundle according to the technical specification, please order the items listed.



PD4N-DALI-SYS

Art.No: 93340


Voltage: via DALI Bus, max. 22.5 V DC
Dimensions: Ø 106 x 68 mm
Settings: B.E.G. DALI-SYS ROUTER /
B.E.G. DALI-SYS PC-Tools



Corridor lens PD4N type A, Cover ring

Art.No: 93741

Detection area: horizontal 360° (Ceiling mounting)
Range: max. Ø 40 m across
max. Ø 20 m towards
Monitored area (tangential movement):
250 m² / 2.5 m mounting height



Wire basket BSK (Ø 200 x 90 mm)

Art.No: 92199

Dimensions: Ø 200 x 90 mm
Impact strength: IK09
Housing: coated steel basket