

B.E.G.**LUXOMAT[®]net**

PD4N-KNXs-BA-FC Set 93535-93314

- Voltage: via KNX BUS
- Dimensions: **Ø 106 x 74 mm + 133 x 133 x 69 mm (93314)**
- Typ. power input: 12 mA

Order data

Designation

PD4N-KNXs-BA-FC

SM socle mounting set IP65 PD4N

Colour

white

white

Art.No

93535

93314

Technical data

| | |
|--|--|
| Voltage: | via KNX BUS Ø 106 x 74 mm + 133 x 133 x 69 mm (93314) |
| Dimensions: | |
| Typ. power input: | 12 mA |
| Detection area: | horizontal 360° (Ceiling mounting) max. Ø 24 m across max. Ø 8 m towards seated |
| Range: | 450 m² / 2.5 m mounting height |
| Monitored area (tangential movement): | 2 m / 10 m / 2.5 m |
| Mounting height min./max./recommended: | |
| Degree / class of protection: | IP20 / Class III + IP65 (93314) |
| Impact strength: | IK04 |
| Ambient temperature: | -25 °C to +55 °C |
| Housing: | polycarbonate, UV-resistant |
| Number of light sensors: | 2 |
| Material color: | white (93314) |
| Number of PIR sensors: | 4 |
| KNX TP 256: | Yes |
| KNX Secure: | Yes |
| Brightness set value: | 5 – 2000 Lux |

Product information

Set : PD4N-KNXs-BA-FC + SM socle mounting set
IP65 PD4N white

KNX occupancy detector with integrated KNX bus connector

KNX Secure ready

Individual adaption of detection sensitivity for each PIR sensor

Mixed light measurement using internal, external and remote (optional) light sensors

Intelligent semi-automatic mode, occupancy-independent regulating mode (photoelectric switch), full automatic mode

1 x light output (for regulating or switching), 1 x slave output

Soft-start

Deactivatable status indicators




Detection area can be extended thanks to master-slave-mode

Extensive optimization options for light measurement

Measured light value is communicated to the bus

Manual influence via external KNX push buttons possible

Behaviour upon bus voltage return definable at choice



Set items

To receive the bundle according to the technical specification, please order the items listed.



PD4N-KNXs-BA-FC

Art.No: 93535

Voltage: via KNX BUS
Dimensions: Ø 106 x 74 mm
Typ. power input: 12 mA



SM socle mounting set IP65 PD4N

Art.No: 93314

Dimensions: 133 x 133 x 69 mm
Degree / class of protection: IP65
Material color: white