



## PD4N-KNXs-DX-FM Bundle 93517-93752-93742

- Voltage: via KNX BUS
- Dimensions: FM= Ø 106 x 55 mm + Ø 109 x 19 mm (93752)
- Typ. power input: 12 mA

### Order data

| Designation                                 | Colour           | Art.No     |
|---|------------------|------------|
| PD4N-KNXs-DX-FM Bundle<br>93517-93752-93742 | traffic<br>white | 1145195142 |

## Technical data

|  |   |
|--|---|
| Voltage:                               | via KNX BUS   |
| Dimensions:                            | FM= Ø 106 x 55 mm + Ø 109 x 19 mm (93752)                 |
| Typ. power input:                      | 12 mA   |
| Detection area:                        | horizontal 360°<br>(Ceiling mounting)<br>(93742)          |
| Range:                                 | max. 40 m x 5 m across<br>max. 20 m x 3 m towards (93742) |
| Monitored area (tangential movement):  | 250 m² / 2.5 m mounting height (93742)                    |
| Mounting height min./max./recommended: | 2.4 m / 2.6 m / 2.5 m (93742)                             |
| Degree / class of protection:          | FM= IP20 / Class III + IP54 (93752)                       |
| Impact strength:                       | IK04  |
| Temperature measurement range:         | -5 °C to +45 °C   |
| Ambient temperature:                   | -25 °C to +55 °C  |
| Housing:                               | polycarbonate, UV-resistant                               |
| Number of light sensors:               | 2   |
| Material color:                        | traffic white mat, similar to RAL9016 (93742)             |
| Number of PIR sensors:                 | 4   |
| KNX TP 256:                            | Yes   |
| Orientation light:                     | 5 – 100 % / OFF / 1 min – 255 min                         |
| Night light:                           | 5 – 100 %   |
| Brightness set value:                  | 5 – 2000 Lux  |

## Product information

Bundle : PD4N-KNXs-DX-FM + SM socle mounting set  
IP54 PD2N- / PD4N-FM traffic white mat, similar to RAL9016 + Corridor lens PD4N type A, Cover ring traffic white mat, similar to RAL9016

KNX occupancy detector with integrated KNX bus connector

KNX Secure ready

HCL/RGB control

Parameterisation from ETS 5 for integration into KNX systems

Individual adaption of detection sensitivity for each PIR sensor

PIR sensors can be deactivated individually

Direction of movement can be identified

Mixed light measurement using internal, external and remote (optional) light sensors

Intelligent semi-automatic mode, occupancy-independent regulating mode (photoelectric switch), full automatic mode

1 x Light (for regulating or switching), 1 x slave output, 3 separate HVAC-blocs

Regulation of up to three lighting groups using offset (external influence possible)

Short presence, self-adjusting follow-up time, corridor function

Various locking functions

Soft-start

Two logic modules

Recall of light scenes

Deactivatable status indicators

Temperature- and noise sensor

The product database for import into the ETS database can be downloaded from the B.E.G. homepage.

Detection area can be extended thanks to master-slave-mode

Extensive optimization options for light measurement

Measured light value is communicated to the bus

Adaption of dimming curve

Bidirectionally remote control-capable with the IR adapter and the B.E.G. smartphone app

PIN code

IR remote control-capable via IR remote control (optionally)

5 button remote control, programmable at choice (accessory)

Programming button (phys. address) can be operated via remote control

HVAC mode (0=automatic, 1=comfort, 2=stand-by, 3=economy, 4=antifreeze/heat protection)

Manual influence via external KNX push buttons possible

Function control (heartbeat, cyclical sending)

Occupancy simulation

Forced switch-off




Intelligent central-off function

Premonition of switch-off

Burn-in function for fluorescent lamps selectable from 1h till 100h

Behaviour upon bus voltage return definable at choice

Variable safety pause after switching off the lights



## Bundle items

To receive the bundle according to the technical specification, please order the items listed.



**PD4N-KNXs-DX-FM**  
Art.No: 93517

Voltage: via KNX BUS  
Dimensions: FM= Ø 106 x 55 mm  
Typ. power input: 12 mA



**SM socle mounting set IP54 PD2N- / PD4N-FM**  
Art.No: 93752

Dimensions: Ø 109 x 19 mm  
Degree / class of protection: IP54  
Housing: polycarbonate, UV-resistant



**Corridor lens PD4N type A, Cover ring**  
Art.No: 93742

Detection area: horizontal 360° (Ceiling mounting)  
Range: max. 40 m x 5 m across  
max. 20 m x 3 m towards  
Monitored area (tangential movement): 250 m² / 2.5 m mounting height