



PD9-M-2C-FC

Prod.No. 92976 EAN: 4007529929764

- Voltage: 110 240 V AC 50 / 60 Hz
- Dimensions: Sensor head: Ø 45 x 28 mm, Power supply: 165 x 24 x 24 mm
- Power consumption: approx. 0.6 W

Order data

DesignationColourArt.NoPD9-M-2C-FCwhite92976

Areas of application

- entrance halls
- corridors/hallways
- small offices

Accessories

Designation	Colour	Art.No
BLE-IR-Adapter	black	93067
IR-PD-2C	-	92475
IR-PD-Mini	-	92159
RC-Arc extinction kit	white	10880
Mini-RC-Arc extinction kit		10882
Cover IP65 for Sensor head PD9	transparent	92958
Cover ring PD9 Ø 36 mm	anthracite	92235
Cover ring PD9 Ø 36 mm	white	92238
Cover ring PD9 Ø 36 mm	silver	92237
Cover ring PD9 Ø 45 mm	white	92327
Cover ring PD9 Ø 45 mm	silver	92346
Square design frame PD9-FC	pure white	92993

Subject to technical changes beg-luxomat.com 01.06.2024

Technical data

110 - 240 V AC Voltage:

50 / 60 Hz

Sensor head: Ø 45 x 28 mm,

Dimensions: Power supply:

165 x 24 x 24

mm

Power consumption: approx. 0.6 W

horizontal 360°

Detection area: (Ceiling mounting)

> max. Ø 10 m across max. Ø 6 m towards max. Ø 4 m

seated

Monitored area (tangential

movement):

Range:

78 m² / 2.5 m mounting height 2 m / 5 m / 2.5

Mounting height min./max./recommended:

Degree / class of protection:

IP20 / Class II

Impact strength: IK03

Ambient temperature: -25 °C to +50 °C polycarbonate,

Housing:

. UV-resistant white mat,

Material color: similar to **RAL9010**

Power consumption: 45 cm, screened

Channel 1 (lighting control)

2300 W, $\cos \varphi =$

1150 VA, $\cos \varphi$ =

0.5

300 W LED

Switching power: max. inrush current lp (20

ms) = 165 A max. inrush current lp (200 μ s) = 800 A 1x μ-contact, NO

contact with tungsten premake contact

5 min - 30 min,

Pulse

Switch-on threshold: 20 - 1000 Lux

Channel 2 (HVAC control potential-free (dry))

Type of contact (k):

Follow-up time:

3 A (230 V), cos Switching power:

 $\varphi = 1$

1x μ-contact, dry Type of contact:

NO contact

5 min - 120 min, Follow-up time:

Pulse

Product information

Mini occupancy detector for light switching with additional

potential-free (dry) contact

Version as master device

Detection area can be extended by using slave devices

Easy operation with remote control (required)

Manual switching via push-button possible

Power supply passes through the hole in the ceiling for the

detector (34 mm Ø)

Spring clips for quick and easy installation in suspended ceilings

and light fittings

Includes 45 mm cover ring and blinds


Factory settings 10 min and 500 lux (15 min HVAC)


Application examples:


entrance halls, corridors/hallways, small offices

Light measuring:

Mixed light measuring







Order data

Designation	Colour	Art.No	EAN
PD9-M-1C-FC-92900	white	92900	4007529929009
PD9-1C-FC-92902	white	92902	4007529929023
PD9-1C-12-48V-FC-92985	white	92985	4007529929856

Accessories



BLE-IR-Adapter Art.No: 93067

Dimensions: 40 x 55 x 103 mm Material color: black

Frequency: 2.4 GHz ISM band, GFSK 0.2

dBm + 5.3 dBi = 5.5 dBm



RC-Arc extinction kit Art.No: 10880

Voltage: 230 V AC \pm 10% Dimensions: 38 x 12 x 26 mm Degree / class of protection: IP20 /

Class II



IR-PD-2C Art.No: 92475

Battery: 3.0 V Lithium CR2032

(inclusive)

Dimensions: 80 x 60 x 8 mm

Material color: -



Mini-RC-Arc extinction kit Art.No: 10882

Voltage: 230 V AC ±10% Dimensions: 50 x 23 x 8 mm Degree / class of protection: IP20 /

Class II



IR-PD-Mini Art.No: 92159

Battery: 3.0 V Lithium CR2032

(inclusive)

Dimensions: 57 x 35 x 7 mm

Material color: -





Cover IP65 for Sensor head PD9 Art.No: 92958

Degree / class of protection: IP65 Material color: transparent



Cover ring PD9 Ø 36 mm Art.No: 92235

Dimensions: Ø 36 mm Housing: polycarbonate, UV-resistant Material color: anthracite glossy



Cover ring PD9 Ø 45 mm Art.No: 92327

Dimensions: Ø 45 mm Material color: white mat



Cover ring PD9 Ø 36 mm Art.No: 92238

Dimensions: Ø 36 mm Housing: polycarbonate, UV-resistant Material color: white glossy



Cover ring PD9 Ø 45 mm Art.No: 92346

Dimensions: Ø 45 mm Material color: silver mat



Cover ring PD9 Ø 36 mm Art.No: 92237

Dimensions: Ø 36 mm Housing: polycarbonate, UV-resistant Material color: silver glossy



Square design frame PD9-FC Art.No: 92993

Dimensions: 45 x 45 x 2.6 mm Housing: polycarbonate, UV-resistant Material color: pure white mat, similar to RAL9010