

**B.E.G.**

**LUXOMAT®**



## PD9-SH-24V-LED Set 93210-92327

Mini-motion detector

For integration into building automation systems

Output 24V DC / 0.5mA

### Order data

Designation	Colour	Art.No
PD9-SH-24V-LED	white	93210
Cover ring PD9 Ø 45 mm	white	92327

## Technical data

Voltage:	24 V DC
Dimensions:	<b>Ø 45 x 28 mm + Ø 45 mm (92327)</b>
Detection area:	horizontal 360° (Ceiling mounting) max. Ø 10 m across max. Ø 6 m towards max. Ø 4 m seated
Range:	78 m <sup>2</sup> / 2.5 m mounting height
Monitored area (tangential movement):	2 m / 5 m / 2.5 m
Mounting height min./max./recommended:	IP20 / Class II
Degree / class of protection:	IK03
Impact strength:	-5 °C to +45 °C
Ambient temperature:	polycarbonate, UV-resistant
Housing:	<b>white mat (92327)</b>
Material color:	350 mm
Cable length:	24V DC / 0.5mA
Switching power:	

## Product information

Set : PD9-SH-24V-LED + Cover ring PD9 Ø 45 mm  
white mat

Mini-motion detector

For integration into building automation systems

Output 24V DC / 0.5mA

93210: With status LED for motion indication



## Set items

To receive the bundle according to the technical specification, please order the items listed.



### **PD9-SH-24V-LED**

Art.No: 93210

Voltage: 24 V DC

Dimensions: Ø 45 x 28 mm

Detection area: horizontal 360° (Ceiling mounting)



### **Cover ring PD9 Ø 45 mm**

Art.No: 92327

Dimensions: Ø 45 mm

Material color: white mat