



PICO-DALI-LINK-FC Set 93908-93776

- Voltage: via DALI Bus, max. 22.5 V DC
- Dimensions: **Ø 45 x 50 mm (93776)**
- Settings: PBM-DALI-LINK-4W-BLE + Smartphone with DALI-LINK App (iOS / Android)

Order data

| Designation | Colour | Art.No |
|-------------------|------------|--------|
| PICO-DALI-LINK-FC | white | 93908 |
| Mounting set PICO | anthracite | 93776 |

Technical data

| | |
|---|---|
| Voltage: | via DALI Bus, max. 22.5 V DC |
| Dimensions: | Ø 45 x 50 mm (93776) |
| Settings: | PBM-DALI-LINK-4W-BLE + Smartphone with DALI-LINK App (iOS / Android) |
| Typ. power input: | 2 mA |
| Detection area: | horizontal 360° (Ceiling mounting) |
| Range: | max. Ø 10 m across max. Ø 6 m towards max. Ø 4 m seated |
| Monitored area (tangential movement): | 78 m ² / 2.5 m mounting height |
| Mounting height min./max./recommended: | 2 m / 5 m / 2.5 m |
| Degree / class of protection: | IP20 / Class II |
| Impact strength: | IK04 |
| Ambient temperature: | -25 °C to +55 °C |
| Housing: | polycarbonate, UV- resistant |
| Material color: | anthracite, similar to RAL7016 (93776) |
| Follow-up time: | 1 sec - 120 min |
| Brightness set value: | 10 - 2500 Lux |

Product information

Set : PICO-DALI-LINK-FC + Mounting set PICO anthracite, similar to RAL7016

Mini DALI multisensor with only 11mm installation depth for installation in luminaires

Powered via DALI bus

Seamless integration in DALI lighting control system B.E.G. LUXOMAT®net DALI-LINK as modular multimaster option

Detection area can be extended thanks to master-slave-mode

Measuring of mixed light thanks to internal light sensor

Semi-automatic, full-automatic or twilight switch mode

Integrated daylight harvesting circuit (or switch output)

Guided Light, Soft-Start PLUS, Orientation light PLUS

Works out-of-the box for easy installation check

Full range of functions can only be activated with other products of the product group B.E.G. LUXOMAT®net DALI-LINK

Detection area can be restricted with blinds

This article is a component of a lighting control system from B.E.G., which supports the use of DALI control gear (luminaires, relays) from other manufacturers

The use of DALI application controllers from other manufacturers is not supported

The use of DALI input devices (sensors, push-buttons) from other manufacturers is not supported

Additional system components (hardware) from B.E.G. are required

Additional free software from B.E.G. is required



Set items

To receive the bundle according to the technical specification, please order the items listed.



PICO-DALI-LINK-FC

Art.No: 93908

Voltage: via DALI Bus, max. 22.5 V DC

Dimensions: Ø 33 x 27 mm

Settings: PBM-DALI-LINK-4W-BLE + Smartphone with DALI-LINK App (iOS / Android)



Mounting set PICO

Art.No: 93776

Dimensions: Ø 45 x 50 mm

Degree / class of protection: IP20

Housing: polycarbonate, UV-resistant