



PL1-30120-LED-AG-DALI-TW

Prod.No. 93066 EAN: 4007529930661

■ Voltage: 200 - 240 V AC 50 / 60 Hz

■ Dimensions: 295 x 1195 x 10 mm

 Luminous flux / intensity: LED circuit board securely mounted
Selectable colour temperatures:
2700 K warm white (3650 lm, 77 lm/W) to 6500 K (4050 lm, 79 lm/W)

Order data

DesignationColourArt.NoPL1-30120-LED-AG-DALI-TWwhite93066

Accessories

Designation	Colour	Art.No
Drop protection PL1-LED	-	93115
Suspension cable set PL1-LED canopy	white	93090
Suspension cable set PL1-LED	-	93173

Technical data

200 - 240 V AC 50 / Voltage:

60 Hz

Dimensions: 295 x 1195 x 10 mm

> LED circuit board securely mounted Selectable colour temperatures:

Luminous flux /

intensity: 2700 K warm white (3650 lm, 77 lm/W)

to 6500 K (4050 lm, 79 lm/W)

Anti-glare: UGR < 19 77 / 79 lm/W Efficiency:

Photobiological

safety:

RG₀

CRI 82 / TM30: 81 Colour reproduction: Rated life time: 60000 h (L80/B10) Power consumption: 45 W / PF 0.89 Degree / class of

protection:

IP20 / Class II

Ambient temperature:

-20 °C to +40 °C

white aluminium

frame Housing:

Lens: plastic diffuser,

white

Material color: white

Product information

LED panel light in very flat design


For installation in suspended ceiling systems Module 600

Adjustable light colour from 2700 K to 6500 K


DALI driver type 8 for colour control

Good glare control through microprismatics UGR < 19

Very uniform illumination of the prismatic cover



h (m)	Ø (m)	E(Ix)
1.0	1.9	1698
2.0	3.9	425
3.0	5.8	189
4.0	7.8	106
5.0	9.7	68



Accessories



Drop protection PL1-LED Art.No: 93115

Dimensions: Length: 1000 mm

Material color: -



Suspension cable set PL1-LED canopy

Art.No: 93090

Dimensions: 295 x 295 x 50 mm, Stahlseillänge

1000 mm Housing: Steel Material color: white



Suspension cable set PL1-LED

Art.No: 93173

Dimensions: Length: 1000 mm

Material color: -