B.E.G. LUXOMAT®



CdS-R

92365 EAN: 4007529923656

230V twilight switch for installation in outdoor lights or junction boxes with an external light sensor

Order data

Designation	Colour	Art.No
CdS-R	black	92365

Technical data

Voltage:	110 – 240 V AC 50 / 60 Hz
Dimensions:	Light sensor Ø 15 x 24 mm, Power supply: 61 x 23 x 38 mm
Power consumption:	< 0.5 W
Degree / class of protection:	Housing IP20 / Light sensor IP54 / Class II
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant
Material color:	black mat, similar to RAL9005
Channel 1 (lighting control)	
Switching power:	1000 W, cos φ = 1 350 VA, cos φ = 0.4
Type of contact (k):	1x µ-contact, NO contact
Switch-on and -off delay:	10 s - 15 s
Switch-on threshold:	2 – 100 Lux

Product information

Photoelectric switch with switch relay

For retrofitting in outdoor lights and for use in branch boxes

Continuously variable twilight value

The cable between the photo sensor and electronic unit is around 15 cm long and may be extended to a maximum of 1.50 m

Application examples: ideal for entrance areas, staircases, halls where permanent light is required


61
11.5
15
23 - 24
Ø 14
max. 10
23
38
16
29 - 34
Ø 14
max. 8