

B.E.G.**LUXOMAT®****10x**

10 x PD3-1C-FC Set 93235-92199

Ceiling motion detector

One channel for light switching

Zero crossing switching

Order data

Designation

10 x PD3-1C-FC

Wire basket BSK (Ø 200 x 90 mm)

Colour

white

white

Art.No

93235

92199

Technical data



Voltage:	110 – 240 V AC 50 / 60 Hz
Dimensions:	Ø 200 x 90 mm (92199)
Power consumption:	< 0.3 W
Detection area:	horizontal 360° (Ceiling mounting) max. Ø 10 m across
Range:	max. Ø 6 m towards max. Ø 4 m seated
Monitored area (tangential movement):	78 m² / 2.5 m mounting height
Mounting height min./max./recommended:	2 m / 5 m / 2.5 m
Degree / class of protection:	IP20 / Class II
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant + coated steel basket (92199)
Material color:	white mat, similar to RAL9010

Channel 1 (lighting control)

Switching power:	2000 W, $\cos \varphi = 1$ 1000 VA, $\cos \varphi = 0.5$ 400 W LED, minimum runtime > 5 min max. inrush current I_p (20 ms) = 80 A
Type of contact (k):	µ-contact, NO contact
Follow-up time:	30 sec – 30 min, Pulse
Switch-on threshold:	10 – 2000 Lux

Product information

Set : 10 x PD3-1C-FC + Wire basket BSK (Ø 200 x 90 mm) white



Set items

To receive the bundle according to the technical specification, please order the items listed.




10 x PD3-1C-FC

Art.No: 93235

Voltage: 110 – 240 V AC 50 / 60 Hz

Dimensions: Ø 85 x 79 mm

Power consumption: < 0.3 W



Wire basket BSK (Ø 200 x 90 mm)

Art.No: 92199

Dimensions: Ø 200 x 90 mm

Impact strength: IK09

Housing: coated steel basket