

B.E.G.

LUXOMAT®

10x



10 x PD3-1C-FC Set 93235-93085

Ceiling motion detector

One channel for light switching

Zero crossing switching

Order data

Designation

10 x PD3-1C-FC

Cover ring PD2/PD3 FC

Colour

white

Art.No

93235

93085

Technical data



Voltage:	110 – 240 V AC 50 / 60 Hz
Dimensions:	Ø 85 x 79 mm
Power consumption:	< 0.3 W
Detection area:	horizontal 360° (Ceiling mounting) max. Ø 10 m across max. Ø 6 m towards max. Ø 4 m seated
Range:	
Monitored area (tangential movement):	78 m ² / 2.5 m mounting height
Mounting height min./max./recommended:	2 m / 5 m / 2.5 m
Degree / class of protection:	IP20 / Class II
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant jet black glossy, similar to RAL9005 (93085)
Material color:	

Channel 1 (lighting control)

Switching power:	2000 W, cos φ = 1 1000 VA, cos φ = 0.5 400 W LED, minimum runtime > 5 min max. inrush current I_p (20 ms) = 80 A
Type of contact (k):	μ -contact, NO contact
Follow-up time:	30 sec – 30 min, Pulse
Switch-on threshold:	10 – 2000 Lux

Product information

Set : 10 x PD3-1C-FC + Cover ring PD2/PD3 FC jet
black glossy, similar to RAL9005



Set items

To receive the bundle according to the technical specification, please order the items listed.



10 x PD3-1C-FC

Art.No: 93235

Voltage: 110 – 240 V AC 50 / 60 Hz

Dimensions: Ø 85 x 79 mm

Power consumption: < 0.3 W



Cover ring PD2/PD3 FC

Art.No: 93085

Dimensions: Ø 84 x 9 mm

Housing: polycarbonate, UV-resistant

Material color: jet black glossy, similar to RAL9005