

**B.E.G.**

**LUXOMAT®**



## BL2-PLUS-FC Set 93405-93256

230V PIR motion detector with 360° detection and a range of up to Ø8m (50 m<sup>2</sup>), remote-controlled

### Order data

Designation	Colour	Art.No
BL2-PLUS-FC	white	93405
Mounting set BL2-SM	white	93256

## Technical data

Voltage:	110 - 240 V 50 / 60 Hz
Dimensions:	<b>Ø 80 x 61 mm + Ø 109 x 50 mm (93256)</b>
Power consumption:	0.3 W
Detection area:	horizontal 360° (Ceiling mounting) max. Ø 8 m across
Range:	max. Ø 4.8 m towards max. Ø 3.2 m seated
Monitored area (tangential movement):	50 m <sup>2</sup> / 2.5 m mounting height
Mounting height min./max./recommended:	2 m / 5 m / 2.5 m
Degree / class of protection:	IP23 / Class II
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant
Material color:	white
Connections and wires:	0.5 - 1.5 mm <sup>2</sup> for solid conductors

### Channel 1 (lighting control)

Switching power:	1000 W, $\cos \varphi = 1$ 500 VA, $\cos \varphi = 0.5$ 400 W LED
Type of contact (k):	1x $\mu$ -contact, NO contact
Follow-up time:	15 sec - 30 min
Switch-on threshold:	10 - 2000 Lux

## Product information

Set : BL2-PLUS-FC + Mounting set BL2-SM white

Remote control-capable occupancy detector for inside use with circular detection area

For mounting in suspended ceilings

One channel for light switching

Manual switching via push-button possible

Basic functions for cost-effective applications


Ready-to-operate thanks to factory settings

Accessory for surface mounting and flush mounting available

Factory setting: High detection sensitivity, follow-up time 10 min, switch-on threshold 500 lux

### Easy operation with remote control (required)

High-performance relay designed for 100,000 switching cycles under high load, several million switching cycles possible under low load





## Set items

To receive the bundle according to the technical specification, please order the items listed.



**BL2-PLUS-FC**  
Art.No: 93405

Voltage: 110 – 240 V 50 / 60 Hz  
Dimensions: Ø 80 x 61 mm  
Power consumption: 0.3 W



**Mounting set BL2-SM**  
Art.No: 93256

Dimensions: Ø 109 x 50 mm  
Degree / class of protection: IP23  
Material color: white