

B.E.G.**LUXOMAT®**

CdS-FC

Prod.No. 92249 EAN: 4007529922499

- Voltage: 110 - 240 V AC 50 / 60 Hz
- Dimensions: Ø 80 x 74 mm
- Power consumption: < 1 W

Order data

Designation	Colour	Art.No
CdS-FC	white	92249

Accessories

Designation	Colour	Art.No
BLE-IR-Adapter	black	93067
IR-CdS-FP	-	92396

Technical data

Voltage:	110 - 240 V AC 50 / 60 Hz
Dimensions:	Ø 80 x 74 mm
Power consumption:	< 1 W
Degree / class of protection:	IP20 / Class II
Impact strength:	IK05
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant
Material color:	white mat, similar to RAL9010

Channel 1 (lighting control)

Switching power:	2000 W, $\cos \varphi = 1$ 1000 VA, $\cos \varphi = 0.5$ max. inrush current I_p (20 ms) = 165 A max. inrush current I_p (200 μ s) = 800 A
Type of contact (k):	1x μ -contact, NO contact with tungsten pre-make contact
Switch-on delay:	determined automatically
Switch-off delay:	5 s - 30 min
Switch-on threshold:	10 - 2000 Lux
Light measuring:	Mixed light measuring

Product information

Remote control-capable photoelectric switch

Extra flat form - only 6 mm high

Adjustable deactivation delay with selflearning deactivation and twilight value

Application examples: ideal for entrance areas, staircases, offices and training facilities



Accessories



BLE-IR-Adapter

Art.No: 93067

Dimensions: 40 x 55 x 103 mm

Material color: black

Frequency: 2.4 GHz ISM band, GFSK 0.2 dBm + 5.3 dBi = 5.5 dBm



IR-CdS-FP

Art.No: 92396

Battery: 3.0 V Lithium CR2032 (inclusive)

Dimensions: 80 x 60 x 8 mm

Material color: -