

B.E.G.

LUXOMAT®



CdS-SM

Prod.No. 92369 EAN: 4007529923694

- Voltage: 110 - 240 V AC 50 / 60 Hz
- Dimensions: 42 x 80 x 96 mm
- Power consumption: < 0.5 W

Order data

| Designation | Colour | Art.No |
|-------------|--------|--------|
| CdS-SM | white | 92369 |

Technical data

| | |
|-------------------------------|-----------------------------|
| Voltage: | 110 - 240 V AC 50 / 60 Hz |
| Dimensions: | 42 x 80 x 96 mm |
| Power consumption: | < 0.5 W |
| Degree / class of protection: | IP54 / Class II |
| Impact strength: | IK01 |
| Ambient temperature: | -25 °C to +50 °C |
| Housing: | polycarbonate, UV-resistant |
| Material color: | white, similar to RAL9010 |

Channel 1 (lighting control)

| | |
|---------------------------|--|
| Switching power: | 2300 W, $\cos \varphi = 1$ 1150 VA, $\cos \varphi = 0.5$ 300 W LED |
| Type of contact (k): | 1x μ -contact, NO contact |
| Switch-on and -off delay: | 1 s - 120 s |
| Switch-on threshold: | 2 - 1000 Lux |

Product information

Photoelectric switch for automatically switching

Activation and deactivation delay with self-learning deactivation-light value

Integrated automatic function (10 Lux / 40 sec. activation / 120 sec. deactivation delay)

LED adjustment aid (without delay) for adjustment of the switch-on threshold

Light value and activation/deactivation delay may be set from the outside using the potentiometer

Double cable inlet from underneath possible

Wall and mast installation



