

B.E.G.**LUXOMAT[®]net**

DA64-230/KNX REG

Prod.No. 93302 EAN: 4007529933020

The gateway connects the KNX BUS with the DALI BUS (DALI BUS for controlling the illumination)

Each gateway is for controlling and dimming up to 64 electronic ballasts in 16 groups

Scenes module for controlling individual electronic ballasts

Order data

| Designation | Colour | Art.No |
|------------------|--------|--------|
| DA64-230/KNX REG | - | 93302 |

Technical data

| | |
|-------------------------------|---------------------------------|
| Voltage: | 230 V AC -15/+10% 50 / 60 Hz |
| Dimensions: | 90 x 72 x 64 mm (4 TE) |
| Typ. power input: | 5.5 mA (KNX, typical) |
| Output voltage: | 16 V DC (DALI, typical) |
| Power consumption: | 0.9 – 6 W |
| Degree / class of protection: | IP20 / Class II |
| Ambient temperature: | -5 °C to +45 °C |
| Housing: | PA66 |
| Material color: | - |
| KNX TP 256: | Yes |
| Nominal current: | 160 mA |
| Nominal current (max.): | 210 mA |

Product information

The gateway connects the KNX BUS with the DALI BUS (DALI BUS for controlling the illumination)

Each gateway is for controlling and dimming up to 64 electronic ballasts in 16 groups

Scenes module for controlling individual electronic ballasts

RGB and TW (DT8) support

Support of B.E.G. DALI-LINK multisensors, push-button modules, push-buttons and DALI relay modules

Commissioning via DCA

Broadcast command via integrated operating buttons

Support for DALI emergency luminaires

Compatible with most DALI drivers or DALI ballasts



