

**B.E.G.**

**LUXOMAT®**



## Indoor 180-R-11-48V-3A covering included Set 92621-92141

- Voltage: 11 - 48 V AC / DC
- Dimensions: **88 x 88 x 42 mm (92141)**
- Power consumption: approx. 1 W

### Order data

#### Designation

Indoor 180-R-11-48V-3A covering  
included

Surface mounting socket Indoor  
180

#### Colour

pure white

pure white

#### Art.No

92621

92141

## Technical data

Voltage:	11 - 48 V AC / DC
Dimensions:	<b>88 x 88 x 42 mm (92141)</b>
Power consumption:	approx. 1 W
Detection area:	horizontal 180° (Wall mounting) max. 10 m across max. 3 m towards
Range:	
Monitored area (tangential movement):	150 m <sup>2</sup> / 1.1 m mounting height
Mounting height min./max./recommended:	1 m / 2.2 m / 1.1 m
Degree / class of protection:	<b>IP54 (92141)</b>
Impact strength:	IK05
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant
Material color:	pure white mat, similar to RAL9010

### Channel 1 (lighting control, potential-free (dry))

Switching power:	3 A; cos $\phi$ = 1
Type of contact (k):	$\mu$ -contact, dry NO contact
Follow-up time:	15 sec - 16 min, Pulse
Switch-on threshold:	5 - 2000 Lux

## Product information

Set : Indoor 180-R-11-48V-3A covering included + Surface mounting socket Indoor 180 pure white mat, similar to RAL9010

Wall motion detector with acoustic sensor, operating voltage 11-48 V

One potential-free switching channel

Acoustic sensor independently adjustable


Noise automatically extends follow-up time

Manual switching via push-button possible

Available with covering (centre plate dimensions 60 x 60 mm) or without covering for use with covering (centre plate dimensions 50 x 50 mm) in 5 different colours

In combination with centre plates usable with current frame systems of various manufacturers

B.E.G. frames and centre plates for combination with other frame systems available



## Set items

To receive the bundle according to the technical specification, please order the items listed.



**Indoor 180-R-11-48V-3A covering included**  
Art.No: 92621

Voltage: 11 - 48 V AC / DC  
Dimensions: covering included 87 x 87 x 61 mm  
Power consumption: approx. 1 W



**Surface mounting socket Indoor 180**  
Art.No: 92141

Dimensions: 88 x 88 x 42 mm  
Degree / class of protection: IP54  
Impact strength: IK05