

B.E.G.**LUXOMAT®**

Indoor 180-R-11-48V-RR covering not included Set 92667-92632

- Voltage: 11 - 48 V AC / DC
- Dimensions: covering not included 70 x 70 x 61 mm
- Power consumption: approx. 1 W

Areas of application

- entrance halls
- corridors/hallways
- staircases
- toilets
- equipment rooms

Order data

Designation	Colour	Art.No
Indoor 180-R-11-48V-RR covering not included	-	92667
Frame IP20 Indoor 180	oyster white	92632

Technical data

Voltage:	11 - 48 V AC / DC
Dimensions:	covering not included 70 x 70 x 61 mm
Power consumption:	approx. 1 W
Detection area:	horizontal 180° (Wall mounting)
Range:	max. 10 m across max. 3 m towards
Monitored area (tangential movement):	150 m ² / 1.1 m mounting height
Mounting height min./max./recommended:	1 m / 2.2 m / 1.1 m
Degree / class of protection:	IP20 / Class II
Impact strength:	IK05
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant
Material color:	oyster white mat, similar to RAL1013 (92632)

Channel 1 (lighting control, potential-free (dry))

Switching power:	0.1 A; $\cos \varphi = 1$ with Reed relay
Type of contact (k):	μ -contact, dry NO contact, with Reed relay
Follow-up time:	15 sec - 16 min, Pulse
Switch-on threshold:	5 - 2000 Lux

Product information

Set : Indoor 180-R-11-48V-RR covering not included + Frame IP20 Indoor 180 oyster white mat, similar to RAL1013

Wall motion detector with acoustic sensor, operating voltage 11-48 V

One potential-free switching channel

Acoustic sensor independently adjustable

Noise automatically extends follow-up time

Manual switching via push-button possible

Available with covering (centre plate dimensions 60 x 60 mm) or without covering for use with covering (centre plate dimensions 50 x 50 mm) in 5 different colours

In combination with centre plates usable with current frame systems of various manufacturers

B.E.G. frames and centre plates for combination with other frame systems available



Set items

To receive the bundle according to the technical specification, please order the items listed.



Indoor 180-R-11-48V-RR covering not included
Art.No: 92667

Voltage: 11 - 48 V AC / DC
Dimensions: covering not included 70 x 70 x 61 mm
Power consumption: approx. 1 W



Frame IP20 Indoor 180
Art.No: 92632

Dimensions: 86 x 86 mm
Degree / class of protection: IP20
Housing: polycarbonate, UV-resistant