

**B.E.G.****LUXOMAT®**

## Indoor 180-S covering included Set 92135-92632-92141

Slave PIR wall-mounted motion detector with 180° coverage and a range of up to 10 m (150 m<sup>2</sup>), for expanding the detection zone

### Order data

Designation	Colour	Art.No
Indoor 180-S covering included	pure white	92135
Frame IP20 Indoor 180	oyster white	92632
Surface mounting socket Indoor 180	pure white	92141

## Technical data

Voltage:	110 - 240 V AC 50 / 60 Hz
Dimensions:	<b>88 x 88 x 42 mm (92141)</b>
Power consumption:	approx. 0.2 W
Detection area:	horizontal 180° (Wall mounting) max. 10 m across max. 3 m towards
Range:	
Monitored area (tangential movement):	150 m <sup>2</sup> / 1.1 m mounting height
Mounting height min./max./recommended:	1 m / 2.2 m / 1.1 m
Degree / class of protection:	<b>IP54 (92141)</b>
Impact strength:	IK05
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant <b>oyster white mat, similar to RAL1013 (92632)</b>
Material color:	
Pulse interval:	2 or 9 sec

## Product information

Set : Indoor 180-S covering included + Frame IP20  
Indoor 180 oyster white mat, similar to RAL1013 +  
Surface mounting socket Indoor 180 pure white mat,  
similar to RAL9010

Slave device

For extending the detection area of a Master device

Compatible with 230 V devices. Concerning exceptions please  
see the respective master device.

Available with covering (centre plate dimensions 60 x 60 mm)  
or without covering for use with covering (centre plate  
dimensions 50 x 50 mm) in 5 different colours

In combination with centre plates usable with current frame  
systems of various manufacturers

B.E.G. frames and centre plates for combination with other  
frame systems available



## Set items

To receive the bundle according to the technical specification, please order the items listed.



**Indoor 180-S covering included**  
Art.No: 92135

Voltage: 110 – 240 V AC 50 / 60 Hz  
Dimensions: covering included 87 x 87  
x 61 mm  
Power consumption: approx. 0.2 W



**Frame IP20 Indoor 180**  
Art.No: 92632

Dimensions: 86 x 86 mm  
Degree / class of protection: IP20  
Housing: polycarbonate, UV-  
resistant



**Surface mounting socket Indoor  
180**  
Art.No: 92141

Dimensions: 88 x 88 x 42 mm  
Degree / class of protection: IP54  
Impact strength: IK05