

**B.E.G.****LUXOMAT®**

## Indoor 180-S covering not included Set 92660-92631

Slave PIR wall-mounted motion detector with 180° detection angle and a range of up to 10 m (150 m<sup>2</sup>), for expanding the detection zone

### Order data

| Designation                        | Colour        | Art.No |
|------------------------------------|---------------|--------|
| Indoor 180-S covering not included | -             | 92660  |
| Frame IP20 Indoor 180              | traffic white | 92631  |

## Technical data

|   |  |
|---|--|
| Voltage:                                  | 110 - 240 V AC<br>50 / 60 Hz                                     |
| Dimensions:                               | covering not<br>included 70 x<br>70 x 61 mm                      |
| Power consumption:                        | approx. 0.2 W  |
| Detection area:                           | horizontal 180°<br>(Wall mounting)<br>max. 10 m                  |
| Range:                                    | across<br>max. 3 m<br>towards                                    |
| Monitored area (tangential<br>movement):  | 150 m <sup>2</sup> / 1.1 m<br>mounting<br>height                 |
| Mounting height<br>min./max./recommended: | 1 m / 2.2 m /<br>1.1 m   |
| Degree / class of<br>protection:          | IP20 / Class II  |
| Impact strength:                          | IK05   |
| Ambient temperature:                      | -25 °C to +50<br>°C  |
| Housing:                                  | polycarbonate,<br>UV-resistant                                   |
| Material color:                           | <b>traffic white<br/>mat, similar<br/>to RAL9016<br/>(92631)</b> |
| Pulse interval:                           | 2 or 9 sec   |

## Product information

Set : Indoor 180-S covering not included + Frame  
IP20 Indoor 180 traffic white mat, similar to RAL9016

Slave device

For extending the detection area of a Master device

Compatible with 230 V devices. Concerning exceptions please  
see the respective master device.

Available with covering (centre plate dimensions 60 x 60 mm)  
or without covering for use with covering (centre plate  
dimensions 50 x 50 mm) in 5 different colours

In combination with centre plates usable with current frame  
systems of various manufacturers

B.E.G. frames and centre plates for combination with other  
frame systems available



## Set items

To receive the bundle according to the technical specification, please order the items listed.



### Indoor 180-S covering not included

Art.No: 92660

Voltage: 110 – 240 V AC 50 / 60 Hz

Dimensions: covering not included 70 x 70 x 61 mm

Power consumption: approx. 0.2 W



### Frame IP20 Indoor 180

Art.No: 92631

Dimensions: 86 x 86 mm

Degree / class of protection: IP20

Housing: polycarbonate, UV-resistant