



L9-LEDN

Prod.No. 94458 EAN: 4007529944583

- Voltage: 230 V AC +/- 10% 50 / 60 Hz
- Dimensions: Ø 475 x 150 mm
- Luminous flux / intensity: LED circuit board securely mounted
Colour temperature: 4000 K neutral white
Luminous flux of LED: 2800 lm
Luminous flux of light 2200 lm
Peak: 559 cd

Order data

Designation	Colour	Art.No
L9-LEDN	white	94458

Technical data

Voltage:	230 V AC +/- 10% 50 / 60 Hz
Dimensions:	Ø 475 x 150 mm LED circuit board securely mounted Colour temperature: 4000 K neutral white
Luminous flux / intensity:	Luminous flux of LED: 2800 lm Luminous flux of light 2200 lm Peak: 559 cd
Efficiency:	92 lm/W
Photobiological safety:	RG 0
Colour reproduction:	CRI 82.1 / TM30: 81.5
Rated life time:	50000 h (L80/B10)
Power consumption:	24 W / PF 0.94
Degree / class of protection:	IP40 / Class I
Impact strength:	IK02
Ambient temperature:	-20 °C to +40 °C
Housing:	Coated sheet steel case with LED circuit board, plastic cover Lens: PMMA diffuser, white
Material color:	white

Product information

Round LED light for wall or ceiling mounting

Energy efficient light with long service life > 50,000 hours

Broad light distribution using diffused light covers

Application examples:

corridors, halls, staircases, storage rooms, cellars, toilets



h (m)	Ø (m)	E (lx)
1.0	3.7	559
2.0	7.5	140
3.0	11.2	62
4.0	15.0	35
5.0	18.7	22



