

B.E.G.**LUXOMAT[®] net**

LK-TP/KNX REG

Prod.No. 90401 EAN: 4007529904013

The device has an extended filter table for main group 0...31 and ensures a galvanic isolation between the lines

The coupler supports KNX longframes and is compatible with the ETS[®] software (ETS4.2 or higher)

The buttons on the front panel allow disabling the telegram filter for testing purposes

Order data

Designation	Colour	Art.No
LK-TP/KNX REG	white	90401

Technical data

Voltage:	via KNX BUS
Dimensions:	90 x 18 x 60 mm (1 TE)
Degree / class of protection:	IP20 / Class III
Ambient temperature:	-5 °C to +45 °C
Housing:	polycarbonate, UV-resistant (PC)
Material color:	white
Connections and wires:	2 x Bus line: EIB/KNX bus terminal (black/red)

Product information

Line coupler in a compact design. It connects two KNX bus segments via twisted pair, for example a KNX line with a KNX area

The device has an extended filter table for main group 0...31 and ensures a galvanic isolation between the lines

The coupler supports KNX longframes and is compatible with the ETS® software (ETS4.2 or higher)

The buttons on the front panel allow disabling the telegram filter for testing purposes

The LEDs indicate operating conditions as well as communication errors on the KNX bus



