



PB8-KNX-ST

Prod.No. 93178 EAN: 4007529931781

- Voltage: via KNX BUS
- Dimensions: 55 x 55 x 25 mm
- Typ. power input: 9.5 mA (typ.) (I_{max} parameterisable 12.5 mA or 20 mA)

Order data

| Designation | Colour | Art.No |
|-------------|--------|--------|
| PB8-KNX-ST | white | 93178 |

Technical data

| | |
|-------------------------------|--|
| Voltage: | via KNX BUS |
| Dimensions: | 55 x 55 x 25 mm |
| Typ. power input: | 9.5 mA (typ.) (I _{max} parameterisable 12.5 mA or 20 mA) |
| Degree / class of protection: | IP20 / Class III |
| Ambient temperature: | -5 °C to +45 °C |
| Material color: | white |
| Display elements: | (2-8) x LED (status; red, green, flashing) 93172: 2 x Push button function 93174: 4 x Push button function 93176: 6 x Push button function 93178: 8 x Push button function |
| Manual operation: | |
| KNX TP 256: | Yes |
| Connections and wires: | 2 x 1 mm pins for bus terminal plug board: 8 pin |

Product information

Binary input device (multi-point pushbutton) for use in 60 mm flush-mounted boxes

Suitable for switch ranges 55x55

Adapter for switch ranges 64x64 included

User-friendly ETS interface

The following functions are possible:

- Switching
- Forced operation
- Percentage
- Temperature
- HVAC mode
- Dimming
- Blinds control
- Scene
- Edge function
- Counter

Settings ex ETS 4 for integration in KNX systems

The product database for import into the ETS database can be downloaded from the B.E.G. homepage.



