

B.E.G.

LUXOMAT[®]net



PBM-KNXs-DX-4W

Prod.No. 93412 EAN: 4007529934126

Binary input or output device (push button interface) for pattress boxes (60 mm)

KNX Secure ready

User-friendly ETS interface

Order data

| Designation | Colour | Art.No |
|----------------|--------|--------|
| PBM-KNXs-DX-4W | | 93412 |

Technical data

| | |
|-------------------------------|---|
| Voltage: | via KNX BUS |
| Dimensions: | 38 x 41 x 12 mm |
| Typ. power input: | 9.5 mA (typ.) (I _{max} parameterisable 12.5 mA or 20 mA) |
| Power consumption: | 0.3 W |
| Degree / class of protection: | IP20 / Class III |
| Ambient temperature: | -5 °C to +45 °C |
| Display elements: | Programming LED |
| KNX TP 256: | Yes |
| KNX Secure: | Yes |
| Cable length: | 270 mm |
| Connections and wires: | plug board: 8 pin Prefabricated connecting wires (extendable to a total of max. 5 m) |
| LED connector: | I _{max} 3.6 mA const. (PWM) LED 3.5 V / 4 mA |

Product information

Binary input or output device (push button interface) for pattress boxes (60 mm)

KNX Secure ready

There are four channels available. Each can either be used as input for a potential-free push-button or switch contact or as binary output for switching a control lamp.

User-friendly ETS interface

The following functions are possible:

- Switching
- Forced operation
- Percentage
- Sequencer
- HVAC mode
- Dimming
- Blinds control
- Scene
- Edge function
- Counter

Parameterisation from ETS 5 for integration into KNX systems

The product database can be downloaded from the B.E.G. homepage or imported directly from the ETS online catalogue



