



PD11-KNXs-FLAT-ST-FC Set 93522-92692

KNX PIR motion detector (standard) with 360°
detection and a range of up to Ø9m (63 m²)

Order data

| Designation | Colour | Art.No |
|----------------------|--------|--------|
| PD11-KNXs-FLAT-ST-FC | white | 93522 |
| Cover ring PD11 | white | 92692 |

Technical data

| | |
|---|---|
| Voltage: | via KNX BUS |
| Dimensions: | Ø 52 x 48 mm + Ø 100 x 3 mm (92692) |
| Typ. power input: | 12 mA |
| Detection area: | horizontal 360° (Ceiling mounting) max. Ø 9 m across max. Ø 6 m towards max. Ø 3 m seated |
| Range: | |
| Monitored area (tangential movement): | 63 m ² / 2.5 m mounting height |
| Mounting height min./max./recommended: | 2 m / 5 m / 2.5 m |
| Degree / class of protection: | IP54 / Class III |
| Impact strength: | IK02 |
| Ambient temperature: | -25 °C to +55 °C |
| Housing: | polycarbonate, UV-resistant white mat, similar to RAL9010 (92692) |
| Material color: | |
| Number of light sensors: | 1 |
| Number of PIR sensors: | 1 |
| KNX TP 256: | Yes |
| KNX Secure: | Yes |
| Orientation light: | 5 - 100 % / OFF / 1 min - 255 min |
| Night light: | 5 - 100 % |
| Brightness set value: | 5 - 2000 Lux |

Product information

Set : PD11-KNXs-FLAT-ST-FC + Cover ring PD11
white mat, similar to RAL9010

Low profile KNX occupancy detector with integrated KNX bus
connector

KNX Secure ready

Parameterisation from ETS 5 for integration into KNX systems

Individual adaption of the PIR sensor sensitivity

Mixed light measurement using internal and remote (optional)
light sensors

Intelligent semi-automatic mode, occupancy-independent
regulating mode (photoelectric switch), full automatic mode

1 x light output (for regulating or switching), 1 x slave output,
3 x HVAC outputs (separately programmable)

Regulation of up to three lighting groups using offset (external
influence possible)

Short presence, self-adjusting follow-up time, corridor function

Various locking functions

Soft-start

Recall of light scenes

Deactivatable status indicators

The product database for import into the ETS database can be
downloaded from the B.E.G. homepage.

Detection area can be extended thanks to master-slave-mode

Extensive optimization options for light measurement

Measured light value is communicated to the bus

Adaption of dimming curve

Bidirectionally remote control-capable with the IR adapter and
the B.E.G. smartphone app

PIN code

IR remote control-capable via IR remote control (optionally)

Programming button (phys. address) can be operated via
remote control

HVAC mode (0=automatic, 1=comfort, 2=stand-by,
3=economy, 4=antifreeze/heat protection)

Manual influence via external KNX push buttons possible

Function control (heartbeat, cyclical sending)

Forced switch-off

Intelligent central-off function

Premonition of switch-off

Burn-in function for fluorescent lamps selectable from 1h till 100h

Behaviour upon bus voltage return definable at choice

Variable safety pause after switching off the lights

Flush mounting with accessory 92833, surface mounting with accessories 92833 and 92121



Set items

To receive the bundle according to the technical specification, please order the items listed.



PD11-KNXs-FLAT-ST-FC
Art.No: 93522

Voltage: via KNX BUS
Dimensions: Ø 52 x 48 mm
Typ. power input: 12 mA



Cover ring PD11
Art.No: 92692

Dimensions: Ø 100 x 3 mm
Housing: polycarbonate, UV-resistant
Material color: white mat, similar to RAL9010