

B.E.G. LUXOMAT[®] net



PD2N-CAS Set 93477-93781-92199

- Voltage: 230 V AC \pm 10% 50 Hz
- Dimensions: **Ø 200 x 90 mm (92199)**
- Settings: Casambi App

Order data

Designation	Colour	Art.No
PD2N-CAS	white	93477
SM socle mounting set IP54 PD2N H	anthracite	93781
Wire basket BSK (Ø 200 x 90 mm)	white	92199

Technical data

Voltage:	230 V AC ±10% 50 Hz
Dimensions:	Ø 200 x 90 mm (92199)
Settings:	Casambi App
Power consumption:	0.5 W
Detection area:	horizontal 360° (Ceiling mounting) max. Ø 10 m across max. Ø 6 m towards max. Ø 4 m seated
Range:	
Monitored area (tangential movement):	78 m ² / 2.5 m mounting height
Mounting height min./max./recommended:	2 m / 5 m / 2.5 m
Degree / class of protection:	IP54 (93781)
Impact strength:	IK09 (92199)
Ambient temperature:	-5 °C to +45 °C polycarbonate, UV-resistant + coated steel basket (92199)
Housing:	anthracite, similar to RAL7016 (93781)
Material color:	
Number of PIR sensors:	1
Channel 1 (lighting control)	
Follow-up time:	1 sec - 60 min
Brightness set value:	1 - 4000 Lux
Light measuring:	Mixed light measuring

Product information

Set : PD2N-CAS + SM socle mounting set IP54 PD2N
H anthracite, similar to RAL7016 + Wire basket BSK
(Ø 200 x 90 mm) white

Casambi-enabled occupancy detector

Mixed light measurement with internal and external light
sensor

Weighting between internal and external light sensor can be
adapted to suit the application

Adjustment of the reflection factor and input of the luminosity
for the display of the actual luminosity in the app

Extension of the detection area with additional B.E.G. Casambi
devices possible

Individual adaption of the PIR sensor sensitivity

Detection area can be restricted with blinds

Functions adjustable via Casambi app

Including pre-assembled spring clamp with strain relief and
contact protection cap for recessed ceiling mounting

Accessory for surface mounting available

Accessories for wall mounting optionally available

Further accessories for colour matching optionally available

Bright LED indication for commissioning



CASAMBI



Set items

To receive the bundle according to the technical specification, please order the items listed.



PD2N-CAS
Art.No: 93477

Voltage: 230 V AC $\pm 10\%$ 50 Hz
Dimensions: $\varnothing 84 \times 85$ mm
Settings: Casambi App



SM socle mounting set IP54 PD2N H
Art.No: 93781

Dimensions: $\varnothing 110 \times 65$ mm
Degree / class of protection: IP54
Material color: anthracite, similar to
RAL7016



Wire basket BSK ($\varnothing 200 \times 90$ mm)
Art.No: 92199

Dimensions: $\varnothing 200 \times 90$ mm
Impact strength: IK09
Housing: coated steel basket