

# B.E.G. LUXOMAT® net



## PD2N-CAS Set 93477-93783

CASAMBI-compatible PIR motion sensor with 360° detection and a range of up to Ø10m (78 m²)

### Order data

Designation	Colour	Art.No
PD2N-CAS	white	93477
SM socle mounting set IP54 PD2N H	black	93783

## Technical data

Voltage:	230 V AC ±10% 50 Hz
Dimensions:	<b>Ø 84 x 85 mm + Ø 110 x 65 mm (93783)</b>
Settings:	Casambi App
Power consumption:	0.5 W
Detection area:	horizontal 360° (Ceiling mounting) max. Ø 10 m across max. Ø 6 m towards max. Ø 4 m seated
Range:	
Monitored area (tangential movement):	78 m <sup>2</sup> / 2.5 m mounting height
Mounting height min./max./recommended:	2 m / 5 m / 2.5 m
Degree / class of protection:	<b>IP54 (93783)</b>
Impact strength:	IK04
Ambient temperature:	-5 °C to +45 °C
Housing:	polycarbonate, UV-resistant
Material color:	<b>black, similar to RAL9005 (93783)</b>
Number of PIR sensors:	1
<b>Channel 1 (lighting control)</b>	
Follow-up time:	1 sec - 60 min
Brightness set value:	1 - 4000 Lux
Light measuring:	Mixed light measuring

## Product information

Set : PD2N-CAS + SM socle mounting set IP54 PD2N  
H black, similar to RAL9005

Casambi-enabled occupancy detector

Mixed light measurement with internal and external light  
sensor

Weighting between internal and external light sensor can be  
adapted to suit the application

Adjustment of the reflection factor and input of the luminosity  
for the display of the actual luminosity in the app

Extension of the detection area with additional B.E.G. Casambi  
devices possible

Individual adaption of the PIR sensor sensitivity

Detection area can be restricted with blinds

Functions adjustable via Casambi app

Including pre-assembled spring clamp with strain relief and  
contact protection cap for recessed ceiling mounting

Accessory for surface mounting available

Accessories for wall mounting optionally available

Further accessories for colour matching optionally available

Bright LED indication for commissioning



# CASAMBI



## Set items

To receive the bundle according to the technical specification, please order the items listed.



**PD2N-CAS**  
Art.No: 93477

Voltage: 230 V AC  $\pm 10\%$  50 Hz  
Dimensions:  $\varnothing 84 \times 85$  mm  
Settings: Casambi App



**SM socle mounting set IP54 PD2N H**  
Art.No: 93783

Dimensions:  $\varnothing 110 \times 65$  mm  
Degree / class of protection: IP54  
Material color: black, similar to RAL9005