

B.E.G.**LUXOMAT®**

PD2N-S Set 93240-93761

Slave PIR motion detector with 360° coverage
and a range of up to Ø10m (78 m²)

Order data

Designation	Colour	Art.No
PD2N-S	white	93240
Cover ring PD2N FM	anthracite	93761

Technical data

Voltage:	110 - 240 V AC 50 / 60 Hz
Dimensions:	Ø 82 x 86 mm
Power consumption:	approx. 0.2 W
Detection area:	horizontal 360° (Ceiling mounting) max. Ø 10 m across max. Ø 6 m towards max. Ø 4 m seated
Range:	
Monitored area (tangential movement):	78 m ² / 2.5 m mounting height
Mounting height min./max./recommended:	2 m / 5 m / 2.5 m
Degree / class of protection:	IP20 / Class II
Impact strength:	IK05
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant
Material color:	anthracite mat, similar to RAL7016 (93761)
Pulse interval:	2 or 9 sec

Product information

Set : PD2N-S + Cover ring PD2N FM anthracite mat,
similar to RAL7016

Slave device detector with circular detection area

For extending the detection area of a Master device

Trigger pulse to master device upon detected movement
independent of the ambient light level

Compatible with 230 V devices. Concerning exceptions please
see the respective master device.



Set items

To receive the bundle according to the technical specification, please order the items listed.




PD2N-S

Art.No: 93240

Voltage: 110 – 240 V AC 50 / 60 Hz

Dimensions: Ø 82 x 86 mm

Power consumption: approx. 0.2 W



Cover ring PD2N FM

Art.No: 93761

Dimensions: Ø 106 x 20 mm

Impact strength: IK05

Housing: polycarbonate, UV-resistant